

ALL FLOOR MECHANICAL VENTILATED LIGHTED & 100% POWER BACKUP. AIR CONDITIONING SYSTEM IS BEIN G PROVIDED. MECHANICAL VENTILATED OUTLET ARE MECHANICAL VENTILATED. THIS SHALL HAVE POWER BACK-UP. ALL ELABORATION OF RELEVANT CODE, PER PROVISION OF RELEVANT CODE, RE-REFIGHTING/SAFETY PROVISIONS WILL BE AS PER RELEVANT CODE PROVISIONS. ASSESSMENT AREA SHALL HAVE MECHANICALLY VENTILATED AS PER RELEVANT CODE. AS PER ARYANA BUILDING CODE, RELEVANT BUILDINGS HAS AUTOMATIC SPRINKLER SYSTEM HAS AUTOMATIC SPRINKLER CODE. BUILDING WILL BE DESIGNED STRUCTURES AS PER RELEVANT CODE. FLOOR PANELS OF FLOURE RES STANDE SHALL BE PROVIDED AS PER RELEVANT CODE. FLOOR PANELS OF PER HARE DAZONING NORMS.

L HANDCAP RAMPS WITH RAILING. L FIRE FIGHTING INSTALLATIONS SHALL BE AS PER PROVISION OF RELEVANT CODE. L THE SAME SHALL BE PROVIDED. L THE SYSTEM SHALL BE PROVIDED AS PER CENTRAL GROUND WATER AUTHORITY NORMS.

PROPOSED BUILDING PLAN OF COMMERCIAL
COMPLEX SITE AREA 1.196 ACRES
43.03 SQM) IN SECTOR 28, GURUGRAM

QUISITIVE INFRADEVELOPERS PVT. LTD.
H LODHA DEVELOPERS LIMITED.

1

For ACQUISITIVE INFRADEVELOPERS PVT. LTD.
Authorized Signatory

Ordering letter No. 8

HSY AREA-CALCU

1

BASEMENT - 03
LVL. -11.300
NO. OF CAR PARKING = 58
HANDICAPPED CAR PARKING = 0
TWO WHEELER PARKING = 13

BASEMENT 03

DAZLEMENT - 03
LVL. -11.300

OF CAR PARKING = 58

WHEELER PARKING = 13

1

Architectural drawing of the basement floor plan for a building. The plan shows various rooms, corridors, and structural elements. Key areas include 'ZONE-O1' (1612,500 SGM) and 'ZONE-O1' (1576,824 SGM). The drawing includes a legend for fire doors, fire exits, and fire alarm devices. It also features a table of fire door ratings and a table of fire door types. The drawing is dated 11/11/2011 and is labeled 'BASEMENT - 03'.

BASEMENT - 03
 V.L. - 11.300
 NO. OF PARKING = 59
 HANDICAPPED PARKING = 01
 TWO WHEELER PARKING = 13

LEGEND

FIRE DOORS

DOOR	Width	Height	Area	Rating	Description
F01	2000	2000	2000	20	Exit door
F02	2000	2000	2000	20	Exit door
F03	2000	2000	2000	20	Exit door
F04	2000	2000	2000	20	Exit door
F05	2000	2000	2000	20	Exit door
F06	2000	2000	2000	20	Exit door
F07	2000	2000	2000	20	Exit door
F08	2000	2000	2000	20	Exit door
F09	2000	2000	2000	20	Exit door
F10	2000	2000	2000	20	Exit door
F11	2000	2000	2000	20	Exit door
F12	2000	2000	2000	20	Exit door
F13	2000	2000	2000	20	Exit door
F14	2000	2000	2000	20	Exit door
F15	2000	2000	2000	20	Exit door
F16	2000	2000	2000	20	Exit door
F17	2000	2000	2000	20	Exit door
F18	2000	2000	2000	20	Exit door
F19	2000	2000	2000	20	Exit door
F20	2000	2000	2000	20	Exit door
F21	2000	2000	2000	20	Exit door
F22	2000	2000	2000	20	Exit door
F23	2000	2000	2000	20	Exit door
F24	2000	2000	2000	20	Exit door
F25	2000	2000	2000	20	Exit door
F26	2000	2000	2000	20	Exit door
F27	2000	2000	2000	20	Exit door
F28	2000	2000	2000	20	Exit door
F29	2000	2000	2000	20	Exit door
F30	2000	2000	2000	20	Exit door
F31	2000	2000	2000	20	Exit door
F32	2000	2000	2000	20	Exit door
F33	2000	2000	2000	20	Exit door
F34	2000	2000	2000	20	Exit door
F35	2000	2000	2000	20	Exit door
F36	2000	2000	2000	20	Exit door
F37	2000	2000	2000	20	Exit door
F38	2000	2000	2000	20	Exit door
F39	2000	2000	2000	20	Exit door
F40	2000	2000	2000	20	Exit door
F41	2000	2000	2000	20	Exit door
F42	2000	2000	2000	20	Exit door
F43	2000	2000	2000	20	Exit door
F44	2000	2000	2000	20	Exit door
F45	2000	2000	2000	20	Exit door
F46	2000	2000	2000	20	Exit door
F47	2000	2000	2000	20	Exit door
F48	2000	2000	2000	20	Exit door
F49	2000	2000	2000	20	Exit door
F50	2000	2000	2000	20	Exit door
F51	2000	2000	2000	20	Exit door
F52	2000	2000	2000	20	Exit door
F53	2000	2000	2000	20	Exit door
F54	2000	2000	2000	20	Exit door
F55	2000	2000	2000	20	Exit door
F56	2000	2000	2000	20	Exit door
F57	2000	2000	2000	20	Exit door
F58	2000	2000	2000	20	Exit door
F59	2000	2000	2000	20	Exit door
F60	2000	2000	2000	20	Exit door
F61	200				

[illegible]

Bathroom Floor		Fire Doors				Description
Door	Width	Height	Material	Set		
1	30"	80"	2400	2400	40	1 1/2" Solid Entry
2	30"	80"	2400	2400	40	1 1/2" Solid Entry
3	30"	80"	2400	2400	40	1 1/2" Solid Entry
4	30"	80"	2400	2400	40	1 1/2" Solid Entry
5	30"	80"	2400	2400	40	1 1/2" Solid Entry
6	30"	80"	2400	2400	40	1 1/2" Solid Entry
7	30"	80"	2400	2400	40	1 1/2" Solid Entry
8	30"	80"	2400	2400	40	1 1/2" Solid Entry
9	30"	80"	2400	2400	40	1 1/2" Solid Entry
10	30"	80"	2400	2400	40	1 1/2" Solid Entry
11	30"	80"	2400	2400	40	1 1/2" Solid Entry
12	30"	80"	2400	2400	40	1 1/2" Solid Entry
13	30"	80"	2400	2400	40	1 1/2" Solid Entry
14	30"	80"	2400	2400	40	1 1/2" Solid Entry
15	30"	80"	2400	2400	40	1 1/2" Solid Entry
16	30"	80"	2400	2400	40	1 1/2" Solid Entry
17	30"	80"	2400	2400	40	1 1/2" Solid Entry
18	30"	80"	2400	2400	40	1 1/2" Solid Entry
19	30"	80"	2400	2400	40	1 1/2" Solid Entry
20	30"	80"	2400	2400	40	1 1/2" Solid Entry
21	30"	80"	2400	2400	40	1 1/2" Solid Entry
22	30"	80"	2400	2400	40	1 1/2" Solid Entry
23	30"	80"	2400	2400	40	1 1/2" Solid Entry
24	30"	80"	2400	2400	40	1 1/2" Solid Entry
25	30"	80"	2400	2400	40	1 1/2" Solid Entry
26	30"	80"	2400	2400	40	1 1/2" Solid Entry
27	30"	80"	2400	2400	40	1 1/2" Solid Entry
28	30"	80"	2400	2400	40	1 1/2" Solid Entry
29	30"	80"	2400	2400	40	1 1/2" Solid Entry
30	30"	80"	2400	2400	40	1 1/2" Solid Entry
31	30"	80"	2400	2400	40	1 1/2" Solid Entry
32	30"	80"	2400	2400	40	1 1/2" Solid Entry
33	30"	80"	2400	2400	40	1 1/2" Solid Entry
34	30"	80"	2400	2400	40	1 1/2" Solid Entry
35	30"	80"	2400	2400	40	1 1/2" Solid Entry
36	30"	80"	2400	2400	40	1 1/2" Solid Entry
37	30"	80"	2400	2400	40	1 1/2" Solid Entry
38	30"	80"	2400	2400	40	1 1/2" Solid Entry
39	30"	80"	2400	2400	40	1 1/2" Solid Entry
40	30"	80"	2400	2400	40	1 1/2" Solid Entry
41	30"	80"	2400	2400	40	1 1/2" Solid Entry
42	30"	80"	2400	2400	40	1 1/2" Solid Entry
43	30"	80"	2400	2400	40	1 1/2" Solid Entry
44	30"	80"	2400	2400	40	1 1/2" Solid Entry
45	30"	80"	2400	2400	40	1 1/2" Solid Entry
46	30"	80"	2400	2400	40	1 1/2" Solid Entry
47	30"	80"	2400	2400	40	1 1/2" Solid Entry
48	30"	80"	2400	2400	40	1 1/2" Solid Entry
49	30"	80"	2400	2400	40	1 1/2" Solid Entry
50	30"	80"	2400	2400	40	1 1/2" Solid Entry
51	30"	80"	2400	2400	40	1 1/2" Solid Entry
52	30"	80"	2400	2400	40	1 1/2" Solid Entry
53	30"	80"	2400	2400	40	1 1/2" Solid Entry
54	30"	80"	2400	2400	40	1 1/2" Solid Entry
55	30"	80"	2400	2400	40	1 1/2" Solid Entry