FORM BR- II (see regulation 3 (i))

SPECIFICATION

The materials used / to be used in the construction is clearly specified under the following heads

	Sr, No	Name	Specifications
	i.	Foundation	RCC strip foundation using M25 grade concrete, Cement Concrete 1:8:16 using brick ballast
	2.	Walls	9" walls in cement mortar 1:4 41/2" walls in cement sand mortar 1:3
			reinforced with hooy iron bond.
	3.	Damp Proof	Horizontal - 1 1/2" Cement concrete 1:4 Vertical - 3/4" cement sand plaster 1:3, treated with two coats of hot bitumen.
	4.	Floor	RCC rough finished or granite/ marble/ ceramic tiles laid over PCC 1:4:8 base to a maximum thickness of 75mm.
	5.	Roofs	RCC (M20 grade) roof with insulation and propriety water proofing.
	6.	Windows / Doors/ woodwork	Teak Wood, champ or marandi, Steel or aluminium
	7.	Steel Work	Tested mild Steel bars @ 96kg/cum.
	8.	Internal Finish	1/2' to 3/4" cement sand plaster in 1:5 with plastic emulsion or distemper paint.
	9.	External Finish	1/2' to 3/4" cement sand plaster in 1:5 with cement colour wash, exposed stone/ clay tile work.
3)		ASTREAM	For Vatika Limited
ż.		TO 3 TIM 3 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Authorised Signatory SIGNATURE OF APPLICANT

SIGNATURE OF ARCHITECT