



- NOTE:
1. ALL WALLS AND PARTITIONS OF THE MAIN AND BASEMENT FLOORS ARE TO BE CONSTRUCTED WITH 200MM THICK CONCRETE BLOCK WORK.
  2. PARTITION WALLS TO THE MAIN ZONING FLOOR ARE TO BE SET OUT TO THE CENTERLINE OF THE WALL.
  3. PARTITION WALLS TO THE BASEMENT FLOOR ARE TO BE SET OUT TO THE CENTERLINE OF THE WALL.
  4. PARTITION WALLS TO THE BASEMENT FLOOR ARE TO BE SET OUT TO THE CENTERLINE OF THE WALL.
  5. PARTITION WALLS TO THE BASEMENT FLOOR ARE TO BE SET OUT TO THE CENTERLINE OF THE WALL.
  6. PARTITION WALLS TO THE BASEMENT FLOOR ARE TO BE SET OUT TO THE CENTERLINE OF THE WALL.
  7. PARTITION WALLS TO THE BASEMENT FLOOR ARE TO BE SET OUT TO THE CENTERLINE OF THE WALL.
  8. PARTITION WALLS TO THE BASEMENT FLOOR ARE TO BE SET OUT TO THE CENTERLINE OF THE WALL.



DATE:	1.10.2020
SCALE:	1:100
PROJECT:	ADAPTIVE REUSE
CLIENT:	ADAPTIVE REUSE
DESIGNER:	ADAPTIVE REUSE
CHECKER:	ADAPTIVE REUSE
APPROVER:	ADAPTIVE REUSE

ADAPTIVE REUSE  
1234567890  
1234567890  
1234567890  
1234567890  
1234567890

NOTES

1. CONSULT THE CLIENT FOR THE LATEST REVISIONS.
2. CONSULT THE CLIENT FOR THE LATEST REVISIONS.
3. CONSULT THE CLIENT FOR THE LATEST REVISIONS.
4. CONSULT THE CLIENT FOR THE LATEST REVISIONS.
5. CONSULT THE CLIENT FOR THE LATEST REVISIONS.
6. CONSULT THE CLIENT FOR THE LATEST REVISIONS.
7. CONSULT THE CLIENT FOR THE LATEST REVISIONS.
8. CONSULT THE CLIENT FOR THE LATEST REVISIONS.
9. CONSULT THE CLIENT FOR THE LATEST REVISIONS.
10. CONSULT THE CLIENT FOR THE LATEST REVISIONS.