

		-, ·.
en spa incs,	CE TO BE LE (In meters)	n'
3		_
5		
6		1
1		-
8		_
10		- 1
11		
12		
13		
14	·	
16		

a) Parking space shell be provided at the rate of 1.5 equivalent car space for each dwalling unit. These parking spaces shall be allotted only to the flat holders and shall not be allotted, leased, sold or transferred in any manner to the third party. The area for parking per car shall be as under : a) December of the target.

- a) Basement. 35 sqm. b) Stilts. 30 sqn).
- c) Open. 25 sam.

c) Open. 25 sqm.
b) At least 75% of the equivalent car spaces shall be provided in the form of covered parking. Further minimum 5% of the total car parking will be made available to the EWS (Category flats.
c) The covered parking in the basement or in the form of multi level parking above ground level shall not be counted towards FAR. It lowever, in case of provision of mechanical parking in the basement for or earling height of the basement for or ceiling height of the basement for or ceiling height of the basement floor y provided towards ground coverage. In case of provision of mechanical parking in the basement floor y provided towards summ of 4.5 mtc. Other than the machanical parking the floor to ceiling height of the basement larger than 2.4 mtc below the hanging beam.
10.UETS AND BAMPS.

10.LIEIS AND BAMPS. Ramps would be optional in Group Housing building in case of 100% stend by generators along with submatic switchover are provided for hunning of lifts along with stairs, However, in case of buildings having more then four storays lifts with 100% stand by generators along with automatic switchover would be essential. Alleast one lift shall be provided with minimum size of 1,00 M X 3.00 M. The clear width of the ramp leading to the basement shall be 4.00 metres with an adequate stope not steeper that 1:10. the proferably at opposite ends. O.LIFTS AND RAMPS.

11.<u>OPEN SPACES</u>. While all the open spaces including those between the blocks and wings of buildings shall be developed, equipped and land scaped according to the plant approved by the D.T.C.P. Haryana, At least 15% of the total site area shall be developed as organised open space i.e tot lots and play ground.

12 APPROVAL OF AUTIDING PLANS:

The building plans of the buildings to be constructed at site shall have to be got approved from the DTCP, Haryana (under section 8(2) of the Act No.41 of 1963), before taking up the construction.

13. DUILDING BYE- LAWS:

The construction of the building/buildings shall be governed by the building rules provided in the part VII of the Punjab Scheduled Roads and Controlled Areas, Restriction of Unregulated Development Rules, 1965. On the points where such rules are silent and stipulate no condition or norm, the model building bye-laws issued by the ISI, and as given in the NBC shall be followed as may be approved by DTCP, Haryana.

A, CONVENIENT, SUDPEING.

- 14,COUVENIENT, SILVEVING.
 0,5% of the toil area shall be reserved to cater for essential convenient schoping with the following conditions.
 a) The ground coverage of 100% with FAR of 100 will be permissible. However this will be a part of the permissible ground Average and FAR of the Group Houring Colony.
 b) The site of Klosk/sliop's shall not be more than 2.75 m to 2.75 m and 2.75 m x 8.25 m.) the height of Klosk/Shops/Departmental Store shall not exceed 4.0
- 15.PROVISION OF COMMUNITY BUILDINGS.
- The community buildings shall be provided as per the composite norms in the Group Housing Scheme.

16.BASEMENT:

16.BASEMENT: Four level basement within the building zone of the site provided it flushes with the ground and is properly landscaped may be allowed. The basement may in addition to parking could be utilized for generator room, lift room, fire Galiling pumps, water reservoir, electric sub-station, air conditioning plants and toilets y utilities, if they satisfy the public health requirements and for no other purposes. Area under stills (only for parking) and basement shall not be council dowards FAR. Dasement shall not be used for storage / commercial purposes but will be subulated and the no other particing on dowards of the main building and it is further than those specified above.

APPROACH TO SITE;

The vehicular approach to the site and parking lots shall be planned and provided giving due consideration to the junctions of and the junctions with the surrounding roads to the satisfaction of the DTCP, Haryana. 18. FIRE SAFETY MEASURES:

a) The owner will ensure the provision of proper fire safety measures in the multi-storeyed buildings conforming to the provisions of Rules 1965/ NBC and the same should be got certified from the competent authority.

b) Electric Sub Station / generator room if provided should be on solid ground near DG/LT. Control panel on ground floor or in upper basement and it should be located on outer periphery of the building, the same should be got approved from the Chief Electrical Inspector Haryana.

19. SOLAR WATER HEATING SYSTEM The provision of solar water heating system shall be as per norms speci by HAREDA and shall be made operational in each building block before applying for an occupation certificate.

(P.P. SINGH) DTP(HQ)

Prinh

20. RAIN WATER HARVESTING SYSTEM. The rain water harvesting system shall be provided as per Central Ground Water Authority norms/Haryana Govt. notification as applicable. 21. The coloniser shall obtain the clearance/NOC as per the provisions of the Notification No. 5.0. 1533 (C) Dated 14.9.2006 issued by Ministry of Environment and Forest, Government of India before starting the construction/ execution of development works at site.

(DHARE SINGH)

/ CTP(HR)

- sopallo

(S.S. DHILLON)

D.T.C.P.(HR

The coloniser/owner shall use only Compact Fluorescent Lamps fittings for internal lighting as well as campus lighting.

DRG. NO. D.T.C.P. 1731 DATED 4: 11: 09