STATE ENVIRONMENT IMPACT ASSESSMENT AUTHORITY HARYANA Bay No. 55-58, Prayatan Blawan, Socior-2, PANCHKULIA.

No. SEIAA/HR/2013 41/8

Dated: 12-7-13

To

M/S Sonika Properties Pvt. Ltd. vt. 33, 25, 25, 25, 25 cm. cycle Proper New Delhi- 110001 (India)

Subjects

Environmental Clearance for construction of "Group Housing Colony" at Sector-36A, Rohlak, Haryana by M/S Sonika Proporties Pvt. Ltd.

Dear Sir.

This letter is in reference to your application no. Nil dated 17-02-2011 addressed to M.S. SEIAA, Haryana received on 21-02-2011 and subsequent letters dated 16-03-2011 and 03-01-2013 seeking prior Environmental Clearance for the above project under the EIA Notification, 2006. The proposal has been appraised as per prescribed procedure in the light of provisions under the EIA Notification, 2006 on the basis of the mandatory documents enclosed with the application viz.. Form: Form: Form: A & Conceptual Plan and additional clarifications familished in response to the observations of the State Expert Appraisal Committee (SEAC) constituted by MOEF. GO: ide their Notification 23.3.2012, in its meeting held on 07-11-2012 and 27-02-2013 awarded "Gold" grading to the project.

Housing Colony" at Sector-36A. Rolatak, Haryana on a plot area of 59945-989 squa. The total built up area shall be 115956.883 squat. The project will comprise 16 flower having + O+1 to 8 + maximum 14 Floors, 880 Dwelling Units, 156 EWS Units convenient shopping and School. The maximum height of the building shall be 51.52 meters. The total water required shall be 744 KLD and the fresh water requirement shall be 470 KLD. The waste water generation shall be 589 KLD, which will be treated in the STP of 700 KLD capacity leading to zero exit discharge. The total power requirement shall be 3358 KVA which will be supported by UHRVN. The Project Proponent has memberal to discharge green belt on 32:32% of project area (22.32% tree plantation + 10% landscaping). The solld waste generation will be 2013 kg/day. The bio-degradable waste will be converted to compost in the project area and manure produced will be used for perticulture and green belt development. The total parting spaces proposed are 1710 ECS.

[3] The State Expert Appraisal Committee, Haryana after the consideration of the relevant documents submitted by the project proponent and additional characteristic furnished in response to us observations have recommended the grant of anvironmental

5_____

clearance for the project mentioned above, subject to compliance with the stipulated conditions. Accordingly, the State Environment Impact Assessment Authority in its meeting held on 27-06-2013 decided to agree with the recommendations of SEAC to accord necessary environmental clearance for the project under Category 8(a) of EIA Notification 2006 subject to the strict compliance with the specific and general conditions mentioned below:-

railt a: SPNCIFIC CONDITIONS:-

- Board under Air and Water Act and a copy shall be submitted to the SEIAA,

 Haryana before the start of any construction work at site.
- [2] A first aid room as proposed in the project report shall be provided both during construction and operational phase of the project.
- (3) Adequate drinking water and sanitary facilities should be provided for construction workers at the site. Provision should be made for mobile toilets. Open defecation by the laboures is strictly prohibited. The safe disposal of waste water and solid wastes generated during the construction phase should be ensured.
- [4] All the topsoff excavated during construction activities should be stored for use in hortfculture/landscape development within the project site.
- [5] The project proponent shall ensure that the building material required during construction phase is properly stored within the project area and disposal of construction waste should not create any adverse effect on the neighboring communities and should be disposed of after taking necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- [6] Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate watercourses and the dump sites for such material must be secured so that they should not leach into the ground water and any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approval of the Haryana State Pollution Control Board.
- [7] The diesel generator sets to be used during construction phase should be of ultra low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
- [8] The diesel required for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
- [9] Ambient noise levels should conform to the residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should

be closely monitored during construction phase. Adequate measures should be taken to reduce ambient air and noise level during construction phase, so as to conform to the stipulated residential standards.

- [10] Fly ash should be used as building material in the construction as per the provisions of Fly Ash Notification of September 1999 and as amended on 27th August 2003.
- [11] Storm water control and its re-use as per CGWB and BIS standards for various applications should be ensured.
- [12] Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other heat practices.
- [13] Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material.
- [14] Opaque wall should meet prescriptive requirement as per Energy Conservation Bullding Code which is proposed to be mandatory for all air conditioned spaces while it is desirable for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
- [15] The approval of the competent authority shall be obtained for structural safety of the building on account of earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightening etc.
 If any forest land is involved in the proposed site, clearance under Forest Conservation Act shall be obtained from the competent Authority.
- [16] The Project Proponent shall provide minimum one hydraulic ladder of sufficient length for escape of people in case of fire.
- [17] The Project Proponent shall submit assurance from the UHBVN for supply of 8358 KVA of power supply before the start of construction. In no case project will be operational solely on generators without any power supply from any external power utility.
- [18] Detail calculation of power load and ultimate power, load of the project shall be submitted to DHBVN under intimation to SEIAA Haryana before the start of construction. Provisions shall be made for electrical infrastructure in the project area.
- [19] The Project Proponent shall obtain NOC from nearest fire station before the start of construction.
- [20] The Project Proponent shall not raise any construction in the natural land depression / Nallah/water course and shall ensure that the natural flow from the Nallah/water course is not obstructed.
- [21] The Project Proponent shall keep the plinth level of the building blocks sufficiently above the level of the approach road to the Project as per prescribed

- by-laws, Levels of the other areas in the Projects shall also be kept suitably so as to avoid flooding.
- [22] Construction shall be carried out so that density of population does not exceed norms approved by Director General Town and Country Department Haryana.
- [23] The project proponent shall not cut any existing tree and project landscaping plan should be modified to include those trees in green area.
- 124] The project proponent shall ensure that ECBC norms for composite climate zone are met. In particular building envelope, HVAC service, water heating, pumping, lighting and electrical infrastructure must meet ECBC norms.
- 125] The project proponent shall provide 3 meter high bardcade around the project area, dust screen for every floor above the ground, proper sprinkling and covering of stored material to restrict dust and air pollution during construction.
- [26] The project proponent shall provide mobile sulabh toilets instead of soak pit during construction phase for disposal of sullage.
- [27] The project proponent shall construct a sedimentation basin in the lower level of the project site to trap pollutant and other wastes during rains.
- [28] The project proponent shall provide proper Rasta of proper width and proper strength for each project before the start of construction.
- [29] The project proponent shall ensure that the U-value of the glass is less than 3.177 and maximum solar heat gain co-efficient is 0.25 for vertical fenestration.
- [30] The project proponent shall adequately control construction dusts like silien dust, non-silica dust, wood dust. Such dusts shall not spread outside project premises.
 Project Proponent shall provide respiratory protective equipment to all construction workers.
- [31] The project proponent shall not restrict the public entry on the kachha rasta and shall maintain the same. Approach to others fand shall be kept free.
- [32] The project proponent shall replace the centrally located water proposed body with green bolt and shall submit the revised plan before the start of construction.
- [33] The project proponent shall ensure plinth level of the building block is 1.5 meter above 100 years flood level.
- The project proponent shall obtain permission of Mines and Geology Department for excevelloit of soll before the after of construction
- [35] The project proponent shall provide one "refuse area" till 24 meter and one till 39 meter as per National Building Code.
- [36] The project proponent shall provide fire control room and fire officer for building above 30 meter as per National Building Code.

2

[37] Rain water harvesting pits have not been proposed. Hence the project proponent shall seek specific approval from HUDA for disposal of excess storm water during rainy season before the start of construction.

Operational Phase:

- [b] The Sewege Treatment Plant (STP) shall be installed for the treatment of the servage to the prescribed atendards including odour and treated effluent shall be recycled. The installation of STP should be certified by an independent expert and a report in this regard should be submitted to the SEIAA, Haryana before the project is commissioned for operation. Tertiary treatment of waste water is mandatory. Discharge of treated sewage shall conform to the norms and standards of HSPCB, Panchkula. Project Proponent shall implement such STP technology which does not require filter backwash.
- Separation of the grey and black water should be done by the use of dual plumbing line. Treatment of 100% grey water by decentralized treatment should be done ensuring that the re-circulated water should have BOD level less than 10 mg/litre and the recycled water will be used for flushing, gardening and DG set cooling etc. to achieve zero exit discharge.
- [d] Por disinfection of the treated wastewater ultra-violet radiation or ozonization process should be used.
- [e] The solid waste generated should be properly collected and segregated. Biodegradable waste shall be decomposed at site and dry/ inert solid waste should be disposed off to approved sites for land filling after recovering recyclable material.
- Diesel power generating sets proposed as source of back-up power for lifts, common aton illumination and for domestic use should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The location of the DO sets should be in the basement as promised by the project proponent with appropriate stack height i.e. above the roof level as per the CPCB norms. The diesel used for DO sets should be ultra low sulphur diesel (0.05% sulphur), instead of low sulphur diesel.
- [8] Ambient Noise level should be controlled to ensure that it does not exceed the prescribed standards both within and at the boundary of the Proposed Residential Complex.
- [h] The project proponent should maintain at least 32.32% as green cover area for tree plantation especially all around the periphery of the project and on the road sides preferably with local species which can provide protection against noise and

suspended particulates matter. The open spaces inside the project should be preferably landscaped and covered with vegetation/grass, herbs & simuls. Only locally available plant species shall be used.

- The project proponent shall strive to minimize water in irrigation of landscape by minimizing grass area, using native variety, xeriscaping and mulching, utilizing efficient irrigation system, scheduling irrigation only after checking evapotranspiration data.
- U) The project proponent shall ensure that the stack height of DG sets is as per the CPCB guide lines and also ensure that the emission standards of noise and air are within the CPCB prescribed limits. Noise and Emission level of DG sets greater than 800 KVA shall be as per CPCB latest standards for high capacity DG sets.
- [1d] The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
- [1] There should be no traffic congestion near the entry and exit points from the roads adjoining the proposed project site. Parking should be fully internalized and no public space should be utilized.
- [m] A report on the energy conservation measures conforming to energy conservation norms finalized by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submitted to the SEIAA, Haryana in three months time.
- [n] Energy conservation measures like installation of LEO for lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use of solar panels must be adapted to the maximum energy conservation.
- [6] The Project Proponent shall use zero azone depleting potential material in insulation, refrigeration, air-conditioning and adhesive. Project Proponent shall also provide halon free fire suppression system.
- [p] The solid waste generated should be properly collected and segregated as per the requirement of the MSW Rules, 2000 and as amended from time to time. The biodegradable waste should be composted by vermi-composting at the site car-marked within the project area and dry/inert solid waste should be disposed off to the highest allowed alter for land dillegation regions alter project area.
- [n] The provision of the solar water heating system shall be as per norms specified by HAREDA and shall be made operational in each building block.
- (r) The traffic plan and the parking plan proposed by the PP should be adhered to methodously with further scope of additional parking for future requirement. There should be no traffic congestion near the entry and exit points from the roads

- adjoining the proposed project site. Parking should be fully internalized and no public space should be used.
- [9] The Project shall be operationalized only when HUDA/public authority will provide domestic water supply system in the area.
- Operation and maintenance of STP, solid waste management and electrical Infrastructure, pollution control measures shall be ensured even after the completion of sale.
- [11] Different type of wastes should be disposed off as per provisions of number and waste, blomedical waste, hazardous waste, c-waste, batteries & plastic rules made under Environment Protection Act, 1986. Particularly E-waste and Baltery waste shall be disposed of as per existing E-waste Management Rules 2011 and Batteries Management Rules 2001. The project proponent should maintain a collection center for E-waste and it should be disposed of to only registered and authorized dismantler / recycler.
- [v] Standards for discharge of environmental pollutants as enshrined in various schedules of rule 3 of Environment Protection Rule 1986 shall be strictly complied with
- [w] Water' supply shall be metered among different residential units and among different utilities.
- [x] All electric supply exceeding 100 amp, 3 phase shall maintain the power factor between 0.98 lag to 1 at the point of connection.
- (y) The project proponent shall use only treated water instead of fresh water for DG cooling. The Project Proponent shall also use evaporative cooling technology and double stage cooling system for HVAC in order to reduce water consumption.
 Further temperature, relative humidity during summer and whater seasons should be kept at optimal level. Variable speed drive, best Co-efficient of Performance, as well as optimal integrated point load value and minimum outside fresh air supply may be resorted for conservation of power and water. Coil type cooling DG Sets shall be used for saving cooling water consumption for water cooled DG Sets.
- [2] The project proponent shall ensure that the transformer is constructed with high quality grain oriented, low loss silicon steel and virgin electrolyte grade copper. The engaged proponent shall obtain manufacturer's cartificate also for that,
- [nn] The project proponent shall ensure that exit volocity from the stack should be sufficiently high. Stack shall be designed in such a way that there is no stack downwater under any meteorological conditions.

PART-B. GENERAL CONDITIONS:

[1] The Project Proponent shall ensure the commitments made in Form-1, Form-1A, BIA/EMP and other documents submitted to the SEIAA for the protection of

environment and proposed environmental safeguards are complied with in letter and spirit. In case of contradiction betwelin two or more documents on any point, the most environmentally friendly compatinent on the point shall be taken as commitment by project proponent.

- (ii) Six monthly compliance reports should be submitted to the HSPCB and Regional Office, MOEP, GOI, Northern Region, Chandigarh and a copy to the SEIAA, Haryana.
- . (III) Noise, STP outlet and stack emission shall be monitored daily. Other cuvironmental parameters shall be monitored on monthly busis. After every 3 months the project proponent shall conduct environmental audit and shall take corrective measure, if required, without dulay.
- [iv] The SEIAA, Haryana reserves the right to add additional safeguard measures subsequently, if found necessary. Environmental Clearance granted will be revoked if it is found that fulse information has been given for getting approval of this project. SEIAA reserves the right to revoke the clearance if conditions stipulated are not implemented to the satisfaction of SEIAA/MoEF.
- [v] The Project proponent shall not violate any judicial orders/pronouncements issued by any Count/Tribunal.
- [vi] All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Avlation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972, Forest Act, 1927, PLPA 1900, etc. shall be obtained, as applicable by project proponents from the respective authorities prior to construction of the project.
- (vii) The Project proponent should inform the public that the project has been accorded Environment Clearance by the SEIAA and copies of the clearance letter are available with the Haryana State Pollution Control Board & SEIAA. This should be advertised within 7 days from the date of issue of the clearance letter at least in two local newspapers that are widely circulated in the region and the copy of the same should be forwarded to SEIAA Haryana. A copy of Environment Clearance conditions shall also be put on project proponent's web site for public awareness.
 - [vili] Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the Project Proposital if it was found that construction of the project has been started before obtaining prior Environmental Clearance.
 - Any appeal against the this Environmental Clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.
 - [x] The project proponent shall put in place Corporate Environment Policy as mentioned in MoEF, Gol OM No. J-11013/41/2006-IA II (I) dated 26.4.2012

within 3 months period. Latest Corpotate flow roument Policy should be submitted to SEIAA within 3 months of issuance of this letter.

- [xt] The fund car-marked for environment protection measures should be kept in separate account and should not be diverted for other purposes and year wise expenditure shall be reported to the SEIA ARC MOEF, Gol under rules prescribed for Environment Audit.
- [xil] The Project Proponent shall obtain NOC will the Aravalli Hotification from CEC of Hon'ble Supreme court regarding poverage under Aravalli Notification before start of construction.
 - [xiii] The Project Proponent shall ensure that no vehicle during construction/operation phase enter the project premises without valid 'Pollution Under Control' certificate from competent Authority.
 - [xlv] The project proponent is responsible for compliance of all conditions in Environmental Clearance letter and project proponent can not absolve himself/herself of the responsibility by shifting it to any contractor engaged by project proponent.
 - [xv] The project proponent shall seek fresh Environmental clearance if at any stage there is change in the planning of the proposed project.

Member Sectetory, State Level Envillement Impact Assessment Authority, Haryana, Panchkula.

Endst. No. SELAA/HR/2013

Dated:....

A copy of the above is forwarded to the following:

- The Additional Director (IA Division). MOEF, GOI, COO Complex, Lodhi Road, New Delhi.
- The Regional office, Ministry of Environment & Forests, Govt. of India, Sector
 31, Chandigarh.
- 3. The Chairman, Haryana State Pollution Control Board, Pkl

Momber Secretary,
State Level Environment Impact
Assessment Authority, Haryana, Panchkula