10.5310 ACRES RESIDENTIAL PLOTTED COLONY UNDER DDJAY IN SECTOR 36, SOHNA

M/S SIGNATURE GLOBAL HOMES PVT LTD

ESTIMATE FOR PROVIDING WATER SUPPLY.SEWERAGE. STORM WATER DRAINAGE, ROADS,STREET LIGHTING AND HORTICULTURE IN RESPECT OF 10.5310 ACRES RESIDENTIAL PLOTTED COLONY IN SECTOR 36,SHONA

INDEX

Sr. No. CONTENTS

- 1 REPORT
- 2 DESIGN CALCULATION
- 3 FINAL ABSTRACT OF COST
- 4 WATER SUPPLY
- 5 SEWERAGE
- 6 STORM WATER DRAINAGE
- 7 ROADS
- 8 STREET LIGHTING
- 9 HORTICULTURE
- 10 MAINTENANCE CHARGES AND RESURFACING OF ROADS
- 11 DESIGN DATA OF ROADS
- 12 DESIGN DATA OF WATER SUPPLY
- 13 DESIGN DATA OF FLUSHINE PIE LINE
- 14 DESIGN DATA OF SEWERAGE
- 15 DESIGN DATA OF STROM WATER DRAINAGE
- 16 LAYOUT DRAWINGS

PROJECT REPORT/ESTIMATE FOR PROVIDING WATER SUPPLY, SEWERAGE, STROM WATER DRAINAGE, ROADS, STREET LIGHTING AND HORTICULURE IN RESPECT OF 10.5310 ACRES RESIDENTAIL PLOTTED COLONY IN SECTOR 36 SOHNA

The Haryana Government has prepared a master plan for development of Residential/Industrial/ Commercial urban estate SHONA, M/S SIGNATURE GLOBAL HOMES PVT LTD has desided to develop a part of the area in this master plan and has named this part as 10,5310 Acres Residential plotted colony. This scheme is located in sector-36 of Haryana Urban Development Authority SHONA.

Water Supply

1 Source

The source of water supply in this area is tubewells at present as the underground water is potable and fit for human consumption. Moreover water is available at reasonable depth. The average yield of tubewell with 40-45 ft strainers will be about 20,000 litre per hour. The recharging of underground water table in this belt is stated to be good. However still we shall resort to rain water harvesting system to keep up the recharging system. The number of tubewells required for the above area has been worked out and the tubewells will be bored in tune with growth of demand to avoid absolence of the tubewells. The ultimate requirement of tubewells includes provisions of 10% stand by. Ultimately, water shall be supplied to the Project by HARYANA URBAN DEVELOPMENT AUTHORITY, SHONA,

2 <u>Design</u>

The scheme has been designed for approved population of **2736 persons**. The rate of water supply per head per day has been taken as 155.25 litres (135+15%)as per NBC 2016 / HUDA norms. in addition to above necessary provision of water for community area, shopping centres, parks etc. have been taken into account for calculating the maximum quantity of water requirement..

3 Pump Chambers and Pumping Machinery

It is proposed to equip each tubewell with an electrically driven set ejecto type or submersible pump capable of delivering of 20,000 litre per hour. It is also proposed to equip required Nos pumping sets with stand by diesel engins /gen set for operation during failure of electricity.

4 Under Ground Storage

Underground storage tank provision has been made for 360KL capacity, in 6 compartments, which caters for the domestic as well as for firefighting requirement, The water for domestic water compartment shall overflow the fire compartment so that the water in the fire compartment also remains fresh.

5 Boosting Station

The boosting is being planned near UGSR catering to the above requirement.

6 Distribution System

The distribution system for this development has been designed to supply @ 155,25 litre per head her day @ 3 times the average rate of flow on Hazen william formula. Necessary provision for laying CI/DI pipes conforming to relevent IS standards along with valves and specials has been made in the project. The minimum terminal head at any point will be more than 27,00 meters so that it can serve the stilt and four floors stories construction envisaged in the plan. Minimum pipe dia for distribution is kept as 100 mm dia. Drinking water supply and 100mm dia for flushing cum irrigation water supply.

7 Rising Mains

Rising mains from HUDA water main or sector road to water works have also been proposed and provision has been made in this estimate.

8 Sewerage

The sewer lines have been designed for 3 times average DWF in relation to the water supply demand assuming that 75% of the domestic water supply shall find its way into the proposed sewer. SW/RCC pipe sewers have been proposed and designed to run half full. The sewers have been designed on 0.77 M per second minimum velocity i.e. self cleansing velocity Necessary provision for laying S.W./R,C.C. pipes manholes etc. has been made in this estimate.

9 Storm Water Drainage

suitable provisions are contemplated in our scheme to ensure better recarging of underground water table in the area R.C.C. Hume pipes drain with minimum 400mm dia is proposed in this area.

10 Roads

The roads in the colony have been planned 9m wide. The following specification have been adopted which are reproduced below.

- (i) _______ 00 mm GSB
- (ii) 250 mm stone aggregate
- (iii) 50 mm thick B.M. DGM
- (iv) 2 mm MSS BC

The above construction shall be done on well compacted sub grade as per specification complete work will be carried out as per Ministry of Road Transport and highways (MORTH) specification, IRC guide lines or HUDA specification, which ever applicable.

11 Street Lighting

The provision has been made on lump sum basis

12 Horticulture

The usual provision of road side plantation of tree guards has been made for all roads. The parks shall be developed by providing lawns etc.

13 Specifications:

The work will be carried out in accordance with the standard sprcification of P.H. Department as laid down by HUDA & Haryana Government.

14 Rates

Estimate for providing services in this pocket has been precared on the recent market rates.

15 Cost

The total cost of development in this project including various P.H. and B & R services works out to Rs 1162.42 Lacs. The cost per gross acre for the phase works out to be Rs 109.43 Lac which covers the provision of services like water supply, sewerage, storm water drainage, roads, street lighting and plantation including maintenance thereof as well as escalation, administrative departmental and unforeseen charges.

The cost per gross acre for this phase works out to **Rs. 109.43 Lacs/acre** which covers the provision of services like water supply, sewerage, storm water drainage, roads, street lighting and plantations including plantations maintenance thereof as well as future expansion whatsoever indicated.

	DESIGN CALCULATION Daily Water Requirement		For 10.5310 Acres	Unit	
	- All (Dans David Auge)		152	Nos	1
	Fotal No. of Plots (Deen Dayal Awas)		0	Nos	1
1	Total No. of EWS Plots				
	⊃opulation per plot (Deen Dayal Awas)		18	Person/Plot	
	Population per plot (EWS)		9	Person/Plot	
1	Population per plot (Evvo)				
	Therefore population (Deen Dayal Awas)		2736	Persons	
	Therefore population(EWS)		0	Persons	
	Total Population		2736	Persons	
	·	SAY	2736	Persons	
	Total daily Water requirement for plots (135 Lpcd + 15%)	@	155.25	Lpcd	
	Total daily Total Conference of the Conference o		424764.00	Lpd	i i
		0.504	424.77	KLD (1)	
		Or Say	424.17	1125 (1)	
	Non residential building water requirement				
	Area of commercial		1	Nos	
	Area of commercial Daily water requirement	@	32000	Ltrs/Acre	
	Area of commercial	•	0.38334	Acre	
	Therefore daily water requirement		12266.94	lit/day	
	The same and the same same same same same same same sam	Or Say	12.27	KLD	
				Man	1
	Area of community center	_	1 25000	Nos lit/day	
	Daily water requirement	@		lit/day	9
	Therefore daily water requirement		25000 25	KLD	
		Or Say	25	KLD	
	Total 2 (a+b)		37.27	KLD (2)	
			0.80	Acre	7
	Area under Parks		25000	lit/acre/day	
	Daily water requirement	@	20044.8	lit/day	
			20.04	KLD	
			2010 .		
			4.03	Acre	Will be
	Area under Roads	@	5000	lit/acre/day	0
	Daily water requirement	@	20172.58	lit/day	grom tre
			20.17	KLD	beom tre
			40.22		eggetten
	Total daily requirement	Total	40.22	KLD	MIN.
)	For (1+2) Dom. Use = 42477+37.27 k		462,04	KLD	
	Hadar Boods Barks (A+5)	L =	40.22	KLD	
)	Under Road+ Parks (4+5) 20,40 + 20,17 KL	•	502.25	KLD	
	Total Daily Requirement		302,20	5	
		Or Say	510.00	KLD	
	Assuming requirement for flushing as 1/3 of total	_	154.01	KLD	
	domestic demand and therefore daily requirement for	x 462.00			
	flushing Or Say	(0.004	155.00	KLD	
			308.02	KLD	
	Daily requirement of portable drinking water supply	154.01	310.00	KLD	
	Or Say	124.0	310.00	KLD	
ı	Tubewell				
1	Assuming working hours of tubewells		16	Hours	
	Assuming working flours of tubewell		20	KL/Hours	
	Assuming discharge/nour or each tubeweil Total domestic water requirment		310	KLD	
	Loral domestic water requirment		0.97		
	No. of tubewells required		-0-40		
			-0.10-	1 19-	
	No. of tubewells required	Total Proposed	1.07 (97 (1W+1S)	

	Pumping machinery for tubewell Gross working load		=		45.00	m	
,	Average Fall in S.L		=		3,00	m	
	Depression head		=		9.00	m	
	Friction loss		=		3.00	m	
1	(Helion loss		=		60,00	m	
		Say	=		60.00	m	
			_		7.40	BHP	
	BHP = $20000x60x1/60x60x75x0.6$		=			BHP	
	With 60% efficiency	Proposed			7.5 0	БПГ	
	It is proposed to install Zno. Submersible pumping	set with a discha	rge of 20000 it	r./hour (335 lp	m) driven with 7.	5 HP electric m	notor each
v	Underground Tank(Drinking water supply)						
•	Daily requirement for domestic use and other except fire fighting		=		308.02	KL	
	Fire Tank Capacity (100ÖP= 100Ö5.76)		=		165.41	KL	
	13 æq.	Say	=		170.00	KL	55.14 KL
					184.81	KL	
	Capacity of under ground tank 60% day except fire fig		=	2 000	KL 190.00	KL	
		Say	=		KL 170.00	KL	
	Fire water storage		=	100	C SHOOD	112	
		Total		3	360-	KL	
	It is proposed to provide 1 no. under ground tank of	0		/tro	10-1 do 100-100		
٧	Tank will have six compartments, two for fire, two for the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water)	raw and the othe the fire compartm	er two for dome nent shall rema	estic use. The v in fresh.	vater first enters th	e fire compart	ment, then over flow
v	the raw water use compartment so that the water in t	raw and the othe	er two for dome nent shall rema	estic use. The vin fresh.	vater first enters th	e fire compart	ment, then over flov
v	the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water) UG. Tank	the fire compartn	er two for domo	e la mesn.	308.02	KL	ment, then over flov
v	the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use	the fire compartn	er two for domo	in nesh.	308.02 19.25	KL KL/HR	ment, then over flov
V	the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand)	the fire compartn	er two for domo	= = Or Say	308.02 19.25 20.00	KL KL/HR KL/HR	
v	the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand)	the fire compartn	er two for domo	= = Or Say =	308.02 19.25 20.00 333.33	KL KL/HR KL/HR LTRS/MI	N
v	the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand)	the fire compartn	er two for domo	= = Or Say	308.02 19.25 20.00 333.33 333.33	KL KL/HR KL/HR	N
V	the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand)	the fire compartn	er two for domo	= Or Say = Or Say	308.02 19.25 20.00 333.33 333.33	KL KL/HR KL/HR LTRS / MI LTRS / MI	N
v	the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts	the fire compartn	er two for domo	= or Say = Or Say =	308.02 19.25 20.00 333.33 333.33 4.0	KL KL/HR KL/HR LTRS / MI LTRS / MI	N
V	the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump	the fire compartn	er two for domo	= Or Say = Or Say = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0	KL KL/HR KL/HR LTRS / MI LTRS / MI m m	N
V	the raw water use compartment so that the water in the BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts	the fire compartn	er two for domo	= Or Say = Or Say = = = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0 4.0 31.0	KL/HR KL/HR LTRS / MI LTRS / MI m m	N
v	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" specials<="" td=""><td>the fire compartn</td><td>er two for domo</td><td>or Say</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0</td><td>KL/HR KL/HR LTRS / MI LTRS / MI m m m</td><td>N</td></main>	the fire compartn	er two for domo	or Say	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0	KL/HR KL/HR LTRS / MI LTRS / MI m m m	N
V	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" specials<="" td=""><td>the fire compartn</td><td>er two for domo</td><td>= Or Say = Or Say = = = =</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00</td><td>KL/HR KL/HR LTRS / MI LTRS / MI m m</td><td>N</td></main>	the fire compartn	er two for domo	= Or Say = Or Say = = = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00	KL/HR KL/HR LTRS / MI LTRS / MI m m	N
v	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" clear="" head="" iii)="" say<="" specials="" td=""><td>the fire compartr</td><td>er two for domo</td><td>or Say</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00</td><td>KL/HR KL/HR LTRS / MI LTRS / MI m m m</td><td>N</td></main>	the fire compartr	er two for domo	or Say	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00	KL/HR KL/HR LTRS / MI LTRS / MI m m m	N
v	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (20*1996*40)="" (4500*75*0.6)<="" bhp="" clear="" head="" iii)="" motor="" of="" say="" specials="" td=""><td>by)</td><td>er two for domo</td><td>or Say</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00</td><td>KL/HR KL/HR LTRS / MI LTRS / MI m m m</td><td>N</td></main>	by)	er two for domo	or Say	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00	KL/HR KL/HR LTRS / MI LTRS / MI m m m	N
V	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (20*1006*40)="" (4500*75*0.6)="" 350<="" bhp="" clear="" head="" iii)="" motor="" of="" say="" specials="" td=""><td>by)</td><td>SAY</td><td>= Or Say = Or Say = = = = = = =</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI m m m m m</td><td>N</td></main>	by)	SAY	= Or Say = Or Say = = = = = = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI m m m m m	N
V	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (20*1000*40)="" (4500*75*0.6)="" 350<="" bhp="" clear="" head="" iii)="" motor="" of="" say="" specials="" td=""><td>by)</td><td>SAY</td><td>= Or Say = Or Say = = = = = = =</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI m m m m m</td><td>N</td></main>	by)	SAY	= Or Say = Or Say = = = = = = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI m m m m m	N
VI	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (="" (20*1000*40)="" (4500*75*0.6)="" 3500="" bhp="" clear="" deleted)="" direct="" head="" iii)="" motor="" of="" over="" process.<="" resorver="" say="" services="" specials="" td=""><td>by)</td><td>SAY</td><td>= Or Say = Or Say = = = = = = =</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI m m m m m</td><td>N</td></main>	by)	SAY	= Or Say = Or Say = = = = = = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI m m m m m	N
	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (="" (20*1006*40)="" (4500*75*0.6)="" 3500="" bhp="" clear="" deleted)="" direct="" head="" iii)="" motor="" of="" over="" purposes<="" resorver="" say="" services="" specials="" td=""><td>by) X 40 X 0.6 o Dumping system Nos.</td><td>SAY adopted)</td><td>= Or Say = Or Say = = = = = = =</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI m m m m m</td><td>N</td></main>	by) X 40 X 0.6 o Dumping system Nos.	SAY adopted)	= Or Say = Or Say = = = = = = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI m m m m m	N
VI	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (="" (20*1000*40)="" (4500*75*0.6)="" 350="" bhp="" clear="" deleted)="" direct="" for="" head="" iii)="" motor="" of="" over="" pumps="" resorver="" say="" services="" specials="" tank<="" td="" ug.=""><td>by) X40 X0.60 Dumping system Nos. 2</td><td>SAY adopted) HP 7,5</td><td>= Or Say = Or Say = = = = = =</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI TM M M M M HP HP</td><td>N N</td></main>	by) X40 X0.60 Dumping system Nos. 2	SAY adopted) HP 7,5	= Or Say = Or Say = = = = = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI TM M M M M HP HP	N N
VI	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (="" (20*1006*40)="" (4500*75*0.6)="" 350="" bhp="" clear="" deleted)="" direct="" flushing<="" for="" head="" iii)="" motor="" of="" over="" pumps="" resorver="" say="" services="" specials="" tank="" td="" ug.=""><td>by) Nos. 2 1</td><td>SAY adopted) HP 7,5 7.5</td><td>= Cor Say = Cor Say = = = = = = = = = = = = = = = = = = =</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP</td><td>N N</td></main>	by) Nos. 2 1	SAY adopted) HP 7,5 7.5	= Cor Say = Cor Say = = = = = = = = = = = = = = = = = = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP	N N
VI	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (="" (20-1006-40)="" (4500*75*0.6)="" 350="" bhp="" clear="" deleted)="" direct="" flushing="" for="" head="" iii)="" motor="" of="" over="" pumps="" resorver="" say="" services="" specials="" tank="" td="" tubewell<="" ug.=""><td>by) X40 X0.60 Dumping system Nos. 2</td><td>SAY adopted) HP 7,5</td><td>e e e e e e e e e e e e e e e e e e e</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP 15 7.5</td><td>N N HP</td></main>	by) X40 X0.60 Dumping system Nos. 2	SAY adopted) HP 7,5	e e e e e e e e e e e e e e e e e e e	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP 15 7.5	N N HP
VI	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (="" (20*1006*40)="" (4500*75*0.6)="" 350="" bhp="" clear="" deleted)="" direct="" flushing<="" for="" head="" iii)="" motor="" of="" over="" pumps="" resorver="" say="" services="" specials="" tank="" td="" ug.=""><td>by) Nos. 2 1</td><td>SAY adopted) HP 7,5 7.5</td><td>= Cor Say = Cor Say = = = = = = = = = = = = = = = = = = =</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI M M M HP HP</td><td>N N HP HP HP</td></main>	by) Nos. 2 1	SAY adopted) HP 7,5 7.5	= Cor Say = Cor Say = = = = = = = = = = = = = = = = = = =	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI M M M HP HP	N N HP HP HP
VI	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (="" (20-1006-40)="" (4500*75*0.6)="" 350="" bhp="" clear="" deleted)="" direct="" flushing="" for="" head="" iii)="" motor="" of="" over="" pumps="" resorver="" say="" services="" specials="" tank="" td="" tubewell<="" ug.=""><td>by) Nos. 2 1</td><td>SAY adopted) HP 7,5 7.5</td><td>e e e e e e e e e e e e e e e e e e e</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP 15 7.5 7.5</td><td>N N HP HP HP</td></main>	by) Nos. 2 1	SAY adopted) HP 7,5 7.5	e e e e e e e e e e e e e e e e e e e	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP 15 7.5 7.5	N N HP HP HP
VI	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (="" (20-1006-40)="" (4500*75*0.6)="" 350="" bhp="" clear="" deleted)="" direct="" flushing="" for="" head="" iii)="" motor="" of="" over="" pumps="" resorver="" say="" services="" specials="" tank="" td="" tubewell<="" ug.=""><td>by) Nos. 2 1 1</td><td>SAY adopted) HP 7.5 7.5</td><td>e e e e e e e e e e e e e e e e e e e</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP 15 7.5 7.5</td><td>N N HP HP HP</td></main>	by) Nos. 2 1 1	SAY adopted) HP 7.5 7.5	e e e e e e e e e e e e e e e e e e e	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP 15 7.5 7.5	N N HP HP HP
VI	BOOSTING MACHINERY (Drinking water) UG. Tank Daily requirement for domestic use Assuming 8 hours running 2 pumps (with one stand) Discharge/hour Head of pump i) Suction lifts ii) Friction loss in M <main &="" (="" (20-1006-40)="" (4500*75*0.6)="" 350="" bhp="" clear="" deleted)="" direct="" flushing="" for="" head="" iii)="" motor="" of="" over="" pumps="" resorver="" say="" services="" specials="" tank="" td="" tubewell<="" ug.=""><td>by) Nos. 2 1</td><td>SAY adopted) HP 7.5 7.5</td><td>e e e e e e e e e e e e e e e e e e e</td><td>308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951</td><td>KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP 15 7.5 7.5 15 45</td><td>N N HP HP HP HP HP KVA</td></main>	by) Nos. 2 1	SAY adopted) HP 7.5 7.5	e e e e e e e e e e e e e e e e e e e	308.02 19.25 20.00 333.33 333.33 4.0 4.0 31.0 39.0 40.00 5.18 3.951	KL KL/HR KL/HR LTRS / MI LTRS / MI m m m HP HP 15 7.5 7.5 15 45	N N HP HP HP HP HP KVA

50

٧	BOOSTING MACHINERY (Flushing water supply)			121	
	Daily requirement for flushing use		154.01	KL	
	Add for horticulture and roads	=	40.22	KL	
	TOTAL	=	194.23	KL	
	Assuming 8 hours running 1 pumps (with one standby)				
	Discharge/hour	32	24.28	KL/HR	
	5.0014.35	Or Say	25,00	KL/HR	
	Discharge/min	: = :	416,67	LTRS / MIN	
		Or Say	416.67-	LTRS / MIN	
	Head of pump	=	4.0	m	
	i) Suction lifts		4.0	m	
	ii) Friction loss in M <main &="" specials<="" td=""><td>=</td><td>31.0</td><td>m</td><td></td></main>	=	31.0	m	
	iii) Clear head	=			
		=	39.0	m	
	Say	=	40.00	m	
	BHP of motor (417*40)/(60*75*0.6) 420 X 40 Capacity of STP SAY		6.22	HP	
	SAY	=	7.5	HP	
	4500 X 0.60				
	Capacity of STP		346.53	KLD	
4	Capacity of STP Sewage load 75 % of total daily water requirement Add 55% for total daily water requirement				
			346.53	KLD	
	Grand Total For 10.5310 Acre		17.32		
			-350.00+ 2	CZ.RCRLD	
	STP Capacity (Or Say)		-000.000	67.07	

Say 365 KLD

FINAL ABSTRACT OF COST Amount (Lacs.) For 10.5310 Ac 209.00 Sub Work 1 Water Supply Rs. 173.88 lay Sub Work 2 Sewerage Re. 98.61 lacs 93.528 Sub Work 3 S.W. Drainage Rs. 116-25 lacs 215.36 Sub Work 4 Roads **Sub Work 5 Street Lighting Sub Work 6 Horticulture** Sub Work 7 Maintenance charges for 10 years i/c resurfacing of roads after 1st 5 years & 2nd 5 years. 1152.42 COST / Acre

10.5310 Ause

Executive Engineer HSVP Divn. No. VI Gurugram

Checked to comments in forward the No. 9.7200 Dt. a. 2) c. 2 2000 and notes attached with the estimate

Superintending Engineer (HQ) for Chief Engineer HSVP

Panchkuta

Superintending Engineer, HSVP Circle-II, Gurugram

Addl. Chief Engineer

CIS

Director

Town and Country Planning, Haryana, Chandigarh WATER SUPPLY HEAD

Sub Head 1 Head Works

Sub Head 2 Pumping Machinery

Sub Head 3 Distribution System(Drinking) & Living main

Sub Head 4 Distribution System flushing cum irrigation

Total

Add 3% Contingencies & PE Charge

Add 49% Departmental Charges, Unfootbear price excolation

Add 49% Departmental Charges, Unfootbear price excolation

Total

(CO to final abstract of cost)

Amount (Lacs.)

For 10.5310 Ac

65.49

22.80

24.91

24.89

24.93

24.93

24.93

24.93

24.93

24.93

25.71

86.44

CO to final abstract of cost)

	Sub Head I				Water Supply Head Works Rs.(lakhs)
S. No. 1	Description Boring and installing 300X200 mm i/d tubewells with reverse/direct rotary rig complete with pipe strainer to a depth of about 150 m, complete,	Unit Nos.	Qty #	Rate ⊘ 00000.00	Re. 10.00 laces
2	Constructing pump chambers as per standard design of PWD PH/HUDA of size 4,90x4.25 m.	Nos.	ŧ	200000.00	2,00
3 a) b)	Construction of boundary wall gate around the Tubewell site, Water Works Tubewells	Nos Nos	ا محر (دیا)	100000.00	1.00 2. 6 0
4	Provision of footpath hodges and lawns at tubewell.	Nos	خه (یما) هه (یما)	100000.00	2.00
5	Construction of boosting chambers of suitable size along with under ground tank of capacity 300 KL pumping machinery and generating set etc. complete in all respects. Details of boosting station				
i)	construction of boosting chamber	LS		52	3,00
ii)	UG tank 360 KL capacity incl. 170 KL for fire fighting.	kl.	360	-10000.00	36.00
	domestic, raw & fire tank in six compartments 85 125	KL	५२८	3500HL	اله.88 لمع
7	Provision for carriage of material and other unforeseen items .	LS			₹.00
8	Provision for staff quarters for Maintenance				2.00
i)	350 sft	Nos.	LS	400000.00	4.00
ii)	440 sft.	Nos.			Ro. 41.88 (qu
iii)	770-sft-	Nos.			P
	(C.O. to abstract of cost of Sub-work No.I)			Total	65.40
1	· W			Say	65.40

	Sub Work I Sub Head No. II				Water Supply Pumping Machinery Amount (Rs.) (in Lakhs)
S. No.	Description	Unit	Qty	Rate	
1	Providing and installing electricity driven electro or submersible pumping set capable of delivering about 20 KL water per hour against a total head of 60 M complete with motor and other accessories. (7.5HP)	Nos.	ŧ	10.00 (ac)	Rs. 10.00 laz
2	Provision for diesel engine genset stand bye arrangements for Tubewells.	Nos.	1	200000.00	2.00
3	Provision for cheap pressure type chlorination plant complete.	Nos.	1	100000,00	1.00
4	Provision for making foundations & erection of pumping machinery.	LS		(40)	R. 1.00
5	Provision for pipes, valves & specials inside the pump chamber.	Nos.	H	200000.00	-4.00-
6	Provision for electric services connection including electric fittings for tubewells chambers complete, Including cost of trasfermer.	LS			2.50
7	Providing and installing centrifugal boosting pumping set, capable of delivering water at 40M head complete in all respects, (7.5HP) (2 working + 1 standby)	Nos.	(241)	1 8 0000.00	3.00lace
8	Providing and installing centrifugal boosting pumping set, capable of delivering water at 40M head complete in all respects. (7.5HP) (1 working + 1 standby)	Nos.	(1+1)	1 6 0000.00	2.00 lacs
9	Providing Gen set 63 KVA.	LS			5.00 leas
10	Provision for carriage of materials and other unforeseen items.	r LS		-	29.00 lay
	(C,O, to abstract of cost of Sub-work No.t)			Total Say	28.00
					Y

	Sub Work I			935	Water Supply
	Sub Head No. III			Di	istribution System/Rising Main
S. No.	Description Providing, laying, jointing & testing D.I. pipes including cost of excavation complete as per ISI marked.	Unit	Qty	Rate	(Domesti C)
		М	11	1575.00	0,17
.,	150 mm dia	M	T791 7	1250.00	9.89
,	100 mm dia	M	36	1000.00 25	D M -0.36
	80 mm dia	M	115	900.00	104 11.78 Cac
iv)	65 mm dia	(VI	942 m		
2	Providing and fixing sluice valves including cost brick masonary chambers complete in all respects.		146 .01		
i)	150 mm i/d	Nos.	1	15000.00	0,15
ii) [100 mm i/d •	Nos.	(147	12000.00	4.68.
	80 mm i/d	Nos:	9 1 4	10000:00 2.5	
7	165 mm i/d	Nos.	[3]	9000.00	0.27 216 64
4	Providing and fixing 150 mm dia NRV including cost of brick masonry chamber.	Nos.	18	10000.00	0.30
5	Providing and fixing 80 mm dia air valves and scour valves including cost of brick masonry chamber.	Nos.	(TO	10000.00	0.20
6	Providing and fixing fire hydrants complete with masonary chambers.	Nos.	13	10000.00	1,30
7	Providing and fixing indicating plates for sluice valve, air valve etc.	Nos.	21	1000,00	0,21
8	Provision for carriage of material & Other und	porseen	(ls)	100000.00	1,00
10	Provision for rising main from tubewells to UG Tank			4050.00	2.25
i)	100 mm	M	180	1250.00	2,25
11	Provision for rising main from main Water supply line to UG Tank (DI Pipe)		000	1250.00	2.98
i)	100 mm	М	238	1250.00	2,00
	(C.O. to abstract of cost of Sub-work No.I)		Total		Q. 31.89-
	(-)		Say		21.89

Sub Work I Sub Head No. IV				Water Supply Flushing and Irrigation
No. Description 1 Providing, laying, jointing & testing D.I. pipes including cost of excavation complete as per ISI marked.	Unit	Qty	Rate	IN LACS
i) 100 mm dia ii) 00 mm dia iii) 103 mm dia	M M M	841 36 86	1250.00 1000.00 MY 900.00	40.51 -0.77 12.00
2 Providing, laying, jointing & testing HDPE (SH80) pipes including cost of excavation complete as per ISI		963 M		
marked.	М	-0-	1250.00	0.00
i) 110 mm dia	M	529-522-	715.00 750	-3.73- 3.91
ii) 75 mm dia	M	0	618.00	0.00
ii) 63 mm dia	M =	26-	415.00	0.15
/) 50 mm dia		186	310.00	0.58
v) 4 0 mm dia	M		240.00 450	0.28 0.53
vi) 32 mm dia for i m fabr	M M	118 11	120.00 350	0.01-
2 Providing and fixing sluice valves including cost brick masonary chambers complete in all respects.				4.00
i) 100 mm i/d	Nos.	15	12000.00	1.80 0.30
ii) 80 mm i/d	Nos.	3	10000.00 9000.00	0.30
iii) 65 mm i/d	Nos	3	5000,00	0,27
3 Providing and fixing 80 mm dia air valves and scour valves including cost of brick masonry chamber.	Nos.	3	10000.00	0.30
4 Providing and fixing indicating plates for sluice valve,	Nos.	24	1000.00	0.24
air valve etc. 5 Provision for carriage of material	LS		100000-00	0,50 0.05
5 Provision for carriage of material				00.04
(C.O. to abstract of cost of Sub-work No.I)		Total		-20.31 4.
/		Say		20.31

					Cowora
	Sub Work II				Sewerage Scheme
S. No.	Description	Unit	Qty	Rate	in Lacs
1	Providing, lowering, jointing, cutting salt glazed stone				
	ware/RCC NP3 pipes and specials into trenches including cost of excavation, bed concrete lot of				
	manholes complete.				
i)	200 mm i/d stone ware Average depth upto 1.5 m	М	484	1250.00	6.05
a) b)	Average depth 1.5 m to 4.5 m	М	209	1600.00	3.34
"	Average department to the the			1200 -	10. 3.14 la
l ii)	250 mm i/d stone ware				0
a)	Average depth 1.5 m to 4.5 m	М	25	1800.00	0.45
					kg 2.0
2	Provision for providing oblique junctions	LS			1G 2
	D. Was fasternoon timboring etc	LS		<u> </u>	1 .0
3	Provision for temporary timbering etc.	20			٨
4	Provision for providing and fixing vent shaft at suitable	LS			2.0
	places as per PH requirements				0
	Provision for cutting of roads and carriage of materials	LS			Ke. 3.0
6	etc. and other unforsean charges				131 130 5-0
		10	odar Part	1.0.	D ₀ 1.0
7	Provision of STP 350 KLD Who to have	ug on ma	MIGN WARE (روی	1. 45.621
.	Provision of STP 369 KLD lebto testaly	LS	(1	(2.1	175_
8		10000			191.84
	Complete	te			64.26
	Add 3% contingencies & PE charges				-5.75632 -19760
- 88					19/603
1	140				96.82
1	Add 49% Deptt. Charges, perce exc	alation	Tot	al	294.42
	(In land on a	J.	100		98.11
	10 C to obstract of cost of Sub-work No. 21	amu.	2	Say	294.42
	(C.O. to abstract of cost of Sub-work No. 2)	dmu,	N.	Say	294

	Sub Work III				Storm water drainage
					a. a.mage
S. No.	Description Providing, lowering, jointing, cutting RCC NP ³ pipes	Unit	Qty	Rate	In Lacs
1	and specials into trenches including cost of excavation cost of manholes, ventilating chambers etc. complete in all respects.				
l n	400 mm i/d				Ro. 24.73 laco
a)	Average depth upto 1.5 m	M	989	2500.00	14.835
b)	Average depth 1.5 m to 4.5 m	М	149	2750.00	4.02 be
2	Provision for road gullies i.e. single and double.	Les Conne	ction (4s)		2.00
3	Provision for lighting, watching and temporary diversion of traffic.	LS		æ	1.00
4	Provision for cutting of roads and carriage of materials etc. and other unforseen items.	LS		180	1.00
5	Provision for temporary disposal arrangements/ Recharge pit. (at selected Places)	Nos	-2-	1500000.00	30,00
6	Provision for connection with HUDA. Swo line	.etec~	aster Road	(23)	1.00
7	Provision for timbering and shoring	LS		÷e	d.500
8	Providing for temprorary disposal arrengment till HUDA service are provided LS	LS		*	10000 Pe .60.94 75: 75 10.60
	Add 3% contingencies & PE Charg	وع)¥	183 2.27 60
	Add 49% Deptt. Charges , Perice exca		unforseer		92.77 78.02 (ac)
1	Λ: 1	dmu.	U	Total	93.63-114
1	(C.O. to abstract of cost of Sub-work No. 1			SAY	93.628 116 % 646

	Sub Work IV				Road Work
S. No.	Description	Unit	Qty	Rate	In Lacs
1	Site Clearance Clearing and grubbing road land including uprooting rank vegetation grass bushesh shrubs saplings and trees girth upto 300mm removal of stumps of trees cut earlier and disposal of unserviceable materials and stacking of serviceable materials to be used or auctioned upto a lead of 1000mm including removable and disposal of top soil not exceeding 150mm thickness by manual means in area of light jungle as per drwing and clause 201 of morth specifications	hectare	1.63	50000.00	-0.82
2	Earth Works Provision for levelling and earth filling as per site conditions.	Acre	10.53125	150000.00	15.80 lags
3	Provisions for 200 mm GSB				
	250 mm thick stone aggregate layer				
	50 mm thick B.M. D&M				2.2/1
	20 mm th M.S.S. & C. Total	Sq. M	7530	1200,00	90.36 des
4 (a		RMT	4892- 2740	600.00	16-44 lans
	946 x 2 = 1892-RM 5 = 27	140	- concent		43.62
(1)	o) Provision of foot path of precast conc. for 10.5310 acres (9m) 9 wide road 946 x 1.2x 2 = 2270.4 SQM Bey	Sq. M	3130	600,00	18.78 bes
4	Provision for indicate plate / guide map/ demarcation	n LS			0,50
	burji etc./ trafīc light etc.				1.00
	Provision for plot indicators LS				≥ .00
l	Provision for demarcating burgies LS				100
	Provision for traffic arrangment		454		
	Provision for carriage of material LS	unfoso	in items (LS	<u> </u>	5:00
	Construction of pavement in shopping area 88+48=13 sqm	6 sqm	77659	600.00	4.66 lace
	Add 3% contingencies & PE charge	<u>د</u> ع			Rs. 140.33 156 -36 lacy
	Add 49% Deptt. Charges, Price exc		, un Lorseer		70.022 161.05 loc
	Admn.		1, 12, 19, 12, 12, 12, 12, 12, 12, 12, 12, 12, 12	Total	215.36- 78.91 la
	C.O. TO FINAL ABSTRACT OF COST SUB WORK			SAY	215.30 239.966

	Sub Work V					Street Lighting
. No. 1	Description Providing street lighting on roads as per standerd specification complete in all respect	Unit	5.	Qty	Rate	in Lacs
	Provision made on L.S. cost @ Rs. 25,0000.00 per acre	L.S.		10.531	250000.00	26.33
						26.33
	Add 29/ contingencies St. Pr. Cl. 2000			5		0.79
	Add 3% contingencies & Pf charges	(e				27.12
	^					13.29
	Add 49% Deptt. Charges, rice Excale	ati'or	- und	30 Seen		15,25
	Add 49% Deptt. Charges, brice Excale		' 0		Total	40.40
	(C.O. TO FINAL ABSTRACT OF COST SUB WORK - V)	-			SAY	R 40.40 6

	Sub Work VI					Horticulture	
	- une sona	Unit	Qty	Rate		Amount	
S. No.		Offic				In Lacs	
1 a)	Development of lawn area Trenching the ordinary soil upto depth of 60 cm. including removal and apcking of servicable material and disposing at the lead of 50m and making upto the tranched area to prope level by filling with earth mixed with manure before and after flooding trenches with water including cost of imported earth and manure.						Ji.
						-	
b) Rough dressing of trenched area.						
						-0.74-	
c) Grassing with(doop grass) including watering and maintenance of lawns free from weds and fit for moving						
	in rows 7.5 cm in either direction including for hedges					1900	
	and grill andbarred wire fencing around park and green belt (as per hudda Norms)	Re. 1.50 lac	s Acre		=	1-20 lacs	
	2 Planting of trees with tree guards on roads at 48						
1	intervals					/	
	total length of roads = 946 mtr No of trees @ 40m c/c = 946x2/40 = 47.3 nos						
	say = 48 nos. Cost of the tree	x2=216	No.				
	Excavation rs 60/-						
	Manure rs 90/- Tree plant rs 150/-					9101-	
	Tree gaurds is 1000/-					2.18 lac	
1	Total = 1300 x 40 2\L					A STATE OF THE PARTY OF THE PAR	
1	213					Rs. y. of lacy	
1	TOTAL					0.04 6 10 1	
	Add 3% contingencies & PE charges					- Oil des	
	3 12 3 3 3	•				1.40 4.73 lace	
	Add 49% Deptt. Charges, Price excala	tion, un	poseen			-0.60 Q. 02 lace	
	Add 49% Deptt. Charges, price excala Adm. Cl	agès.	· ·	Total		2.09	
	C.O. TO FINAL ABSTRACT OF COST SUB WORK	•		SAY		2.00 6. S lace	
	COLIO I HAVE UPP LINES						

Maintenance Sub Work VII Rate In Lacs Qty Unit Description S. No. Provision for maintenance charges for water supply, 1 sewerage, storm water drainage, roads, street light, horticulture etc. complete including operation and establishment charges as per HUDA norms after completion and resurfacing of roads after 10 years or 1st phase. 78.98 750000.00 10.531 Acre 600.00 8514 Provision for resurfacing of roads after 1st five years of Sq. M 2 maintenance (as per details attached). Area in Sqm. 1530 Provision for resurfacing of road after 10 years 750.00 8514 Sq. M @ Rs.750/- per sqm. 7530 193.92 Add 3% contingencies & PE Charges 5.82 rice excalation, unforseen Total 297.61 (C.O. TO FINAL ABSTRACT OF COST SUB WORK -SAY