

STP FEASIBILITY REPORT **(HT-SBR)**

Date of Submission: 09-05-2022.



Project Report - Sewage Treatment Plant

INTRODUCTION

M/s. MVN Athens, Sector-05 Sohna, District-Gurgaon, Haryana, have proposed residential development at Sector-05 Sohna, District-Gurgaon, Haryana. With a view to conserve fresh water resources and adopt re cycle and re-use measures. They propose to set up a water pollution control and re-use system for the wastewater generated from entire complex and also proposed to harvest and recharge ground water as storm water management. The only source of wastewaters is from toilets, pantries and washbasins and washrooms therefore domestic in nature. One number of STP has been proposed for the entire Residential Apartments & Villas.

This report details the following from the proposed facility. Collection, treatment and Disposal of Domestic Effluents.

QUANTITY AND QUALITY OF WASTEWATERS

The wastewater quantity from domestic sources is considered at maximum of 85% of water consumed. Hence the quantity of wastewater generated is as below

Total Quantity of wastewater generated = 700.00KLD

1 No Sewage Treatment plant for treating sewage has been proposed with capacity of 700.0 Cum/day respectively.

The **Advanced Sequential Bio Reactor treatment process (SBR)**

1.1 Plant Capacity

The sewage treatment plant is designed to treat 700 m³/day of domestic sewage. The plant is designed to operate at a flow rate / stream of 35.0 m³/hr in 20 hours operation. The SBR system is designed on the following basis: -

Particulars	Typical value
Flow /Stream	35.0 cum/hr
No of Streams	1 Nos
Nature of Waste	Domestic Sewage
Total Plant Area	400m ²
Total Plant Depth	10m

1.2 Water Quality

The Sewage Treatment Plant (STP) receives raw sewage water to the Bar Screen followed by raw sewage collection Sump. The plant is designed to take care of sewage treatment applications for 700 m³/d flow. The operating characteristics of the plant are as follows:

Table 1: Typical Water Quality in Bioreactor

Parameters	Range
Flow / Stream	35.0 m ³ /day
No of streams	1 Nos
Nature of Waste	Domestic Sewage
pH	5.5 - 7.5
BOD ₅	200 - 250 mg/l
COD	400 - 600 mg/l (Max)
TSS	30-50 mg/l
Oil and Grease	30-50 mg/l (max)

Oil and grease removal is ensured by properly designed grease trap and oil skimming method adopted in the plant.

Treated Sewage Quality

Table 1: Typical Water Quality at outlet end.

Parameters	Range
pH	6-8.0
BOD ₅	Less than 10 mg/l
COD	Less than 50 mg/l
TSS	Less than 10 mg/l
Oil and Grease	Less than 20 mg/l
E-Coli	Nil

DURATION OF OPERATION

The entire system will operate for 20 hrs, as needed, for the treatment of **700 m³ / day. All pumps and blowers will be provided with standby.**

Process Design Description


Pre-treatment

Raw wastewater entering the STP must be screened with a bar screen of size 10-25 mm before entering the bioreactor portion of the SBR process to remove coarse aggregates, etc.

Grease Trap

Fat, oil and grease will effect the process and also effects quality of treated water. Hence an effective grease trap system (Like Hydro Treat Belt Type Oil Skimmer) must be incorporated at the inlet end before the bar screen chamber in order to remove oil and grease to treatable limits.

PROCESS DESCRIPTION FOR ADVANCED SEQUENTIAL BIO- REACTOR (SBR)



SCREENING

Sewage is directed into a bar screen chamber for removal of floating material such as grass, polythene bags etc. A manual coarse-bar-screen is provided for separation, thereby protecting the subsequent process equipment from damage and improving the reliability and effectiveness of the process.

OIL & GREASE REMOVAL

Oil in sewage forms scum and can interfere with the biological process. Sewage from bar screens passes through the Oil & Grease Trap for removal of Oil, Fats or other greasy matter from sewage.

AERATION, CLARIFICATION & DECANTING

There are two no's of Reactor in which sewage undergoes unit operations of Aeration, Settling and Decanting.

Reactor is a self-contained system incorporating equalization, aeration and clarification within the confines of a **SINGLE** basin for Each Reactor. It uses a state-of-the-art Biomass Conditioning technology, which enables the system to attain nutrient control without the addition of chemicals and to outperform continuous "flow through systems". All the treatment processes take place in the reactor tank thus eliminating the need for clarifiers. This process treats the wastewater in a batch mode and each batch is sequenced through a series of treatment stages.

The process follows five basic stages :

- 1) **FILL**
- 2) **REACT**
- 3) **SETTLE**
- 4) **DECANT**
- 5) **IDLE**

The actual cycle time will vary with the effluent results desired. If only BOD reduction is desired, a cycle time of 3 hours may be used. All the three phases are logically time- controlled.

Typical Cycles:

FILL : The influent wastewater is distributed into the sludge blanket and can take place under mixed or unmixed conditions and aerated or un-aerated conditions.

REACT : This includes mixing and aeration. Aerated conditions serve to oxidize organic carbon, nitrify ammonia, and promote uptake of phosphorus in the sludge. Un-aerated conditions promote de-nitrification of nitrite and nitrate.

SETTLE : During this cycle, all mixing and aeration is turned off and the mixed liquor Solids settle, allowing a clear supernatant to form in the upper part of the tank.

DECANT : The decant event occurs after a substantial depth of supernatant has formed. Automatic valves open and supernatant is drawn off the upper portion of the tank. Sludge wasting can occur during this time, because the settled sludge bed would attain a maximum concentration of solids.

IDLE : This is a unique stage which helps in acclimatisation for the biomass for the fill Stage and also helps in the reduction of Phosphorous.

DISINFECT : Done using a highly effective Chlorination system which does not leave a residue after the reaction.

❖ **General:**

The duration of the various steps is controlled by Manually with Valves. The timing of each step is preset by Operators Present at site. The timings of the steps of chemical cleaning are also set By Operators Present at site. The duration of various steps can be changed by Operators Present at site..

Each step of the operation can be set and monitored from the operator. Interface located on the panel.

The operational control of the plant and its monitoring is carried out through a number of graphic screens provided on the operator station. The screens include time settings, elapsed time of each step of operation, shut down valve status, etc.

Following are description of individual treatments units, with their sizes and Mechanical Equipments required.

DESIGN CALCULATION OF TREATMENT UNITS

Flow : 700 KLD

1. Bar Screen Chamber

$$\text{Flow} = \frac{700}{24} = 29.17 \text{ m}^3/\text{hr}$$

Say 35.0 Cum/hr

Factor of safety = 1.5 ; Design flow = $35 \times 1.5 = 52.5 \text{ m}^3/\text{hr}$ &

$$\frac{52.5}{60 \times 60} = 0.0146 \text{ m}^3/\text{sec}$$

Function : to eliminate Solids > 20 mm

Coarse Screen and Fine Screen total No. = 1 No.

Inflow velocity = 0.45 m/sec

Angle of Inclination = 60°

Clean opening a) Coarse Screen - 25 mm

b) Fine Screen -10 mm

$$\text{Cross Section of Screen Chamber} = \frac{0.00166}{0.45} = 0.00368 \text{ Sqm}$$

2. Equalization Tank

Average flow = 700 m³ / stream / day

Peak flow 700 m³ / day @ 24 hrs flow duration

$$\text{Flow} = \frac{700}{24} = 35.0 \text{ m}^3/\text{hr}$$

Say 35.0 Cum/hr

Keeping 8.6 hrs detention period

$$\text{Volume of tank} = 35.0 \times 8.6 = 301.0 \text{ m}^3$$

Provide Size per tank = 25.2 Sqm x 5.5 m SWD

To suit accommodate the space available @ site.

3. Bio-Reactor (SBR)

The following design assumptions and conditions are considered.

No. of Bio-reactors = 2 Nos.

Liquid depth = 4.5 m

Decant depth is 33% of the total water depth = 1.48 m

Overall hydraulic retention time = 20 hrs

F/M = 0.1

MLSS = 2400 mg/lit

$$\text{Total volume of the reactor} = \frac{240 \times 240}{0.1 \times 2400} =$$

Say

$$= 240 \text{ cum}$$

Provided Each reactors of 240Cum (4m SWD) - 2 Nos.

Check for Detention time = $\frac{\text{Volume of the Reactor}}{\text{Design flow}}$

$$= \frac{240}{24.0} = 10.0 \text{ hrs (Hence ok.)}$$

Total cycle time = time fill + time aeration + time decant + time settling/

$$= 2 + 3 = 5 \text{ hrs}$$

$$\text{Number of cycles/tank/day} = \frac{24 \text{ hrs}}{5} = 5 \text{ cycles/tank/day}$$

4.5 hrs/d

Number of cycles /day = 4.5 cycles/day

Fill volume/ cycle = $\frac{700}{4.5} = 155.55 \text{ m}^3$

a) Oxygen requirement

Organic Load (kg of BOD) = $700 \text{ KLD} \times 0.250 = 175 \text{ kg / day}$

Oxygen requirement = 2 time of organic load.

= $2 \times 175 = 350 \text{ kg / day}$

Considering O_2 diffusion rate @ 18 gm / m^3 of air volume per running „M“ of depth of water and considering 60% efficiency of air blower and at working 24 hrs / day.

Air requirement for SBR Tank = $\frac{700 \times 1000}{24 \times 18 \times 4.5 \times 0.6} = 600.13 \text{ m}^3/\text{hr}$

Air required for Equalization tank = $0.9 \times \text{Volume of Equalization Tank}$
 = 0.9×300
 = $270 \text{ m}^3 / \text{hr}$

Air required for Sludge Holding tank = $0.3 \times \text{Air required for ET}$
 = 0.3×71.2
 = $21.36 \text{ m}^3/\text{hr} \times \text{Detention time} \times 0.9$
 = $21.36 \times 2.2 \times 0.9$
 = $42.29 \text{ m}^3/\text{hr}$

Total air required (m^3/hr) $600.1 + 270.0 + 42.29 = 912.42$

There fore Provided 3 Nos air blower each $500 \text{ m}^3 / \text{hr}$ @ 5000 MMWG - (2 Working + 1 SB)

b) Fine Bubble diffusers

No. of fine bubble diffusers of 1 m long required @ the air distribution rate of 8 m³/hr/m length of diffuser as discharge rate.

Running Meters = $\frac{601}{8} = 74$ Rmts, Provide 37 Rmts in each tank

1. FILTER FEED PUMPS

Flow = 700 m³ / day

At 20 hrs Working

Flow = $\frac{700}{20} = 35.00$ m³ / hrs.

Provide 35.0 m³/hr @ 20 m head.- (1Working + 1SB)

Type of Pumps - Horizontal Centrifugal, close impeller.

2. PRESSURE SAND FILTER

Considering rate of filtration @ 35 m³/hr/m²

Therefore provide 1 No. each 1.5 m dia filter.

Type - Vertical, sand filters

Media - Pebbles, Gravel, Sand

3. ACTIVATED CARBON FILTER

Provide 1 Nos. each 1.5 m dia

Type - Vertical, Carbon filter

Media - Pebble, Gravel, sand and Activated carbon granules of 500 grade.

4. SLUDGE RECIRCULATION PUMPS

Flow - 10m³ / hr @ 10 m head

Qty - 1 No.

Type - Horizontal, non-clog, centrifugal, open impeller

CHLORINATION

Chemical type - Liquid Hypo chlorite

Dosage = 4 to 5 mg / ltr.

Chlorine required per day = $0.8 \times 2 = 1.6$ kg / day

Dosing pump required @ 20 hrs working = $\frac{1.6 \times 700}{20} = 56.0$ gm / hr

Type of Chlorine dozer pump = electronic dosing

Capacity - 1 to 4 LPH @ 4.0 kg / cm² pressure.



7. FILTER PRESS

a. Filter Press

Type - Recessed type, hydraulic closing manual operating system

Size : 600mm X 600mm

M.O.C. - Polypropylene, plates - 24 Nos.

Test pressure - 5 kg / cm²

Closing pressure - 200 to 250 kg / cm²

Filter Cloth - PP, 5-micron size

No. of units - 1 No.

b. Screw Pump

Filter Press Feed Pump type - Screw Pump

Capacity - 3.0 m³ / hr @ 40 m head

Qty - 1 No.

