ACRES OF COMMERCIAL COLONY AT VILLAGE WAZIRPUR, SEC-95A, GURUGRAM, HARYANA

DEVELOPED BY M/S MICROTEK URBAN DEVELOPER'S PVT LTD

OF 4 ACRES OF COMMERCIAL COLONY AT VILLAGE WAZIRPUR, SEC-95A, GURUGRAM, HARYANA ESTIMATE FOR PROVIDING WATER SUPPLY.SEWERAGE. STORM WATER DRAINAGE, ROADS, STREET LIGHTING AND HORTICULTURE IN RESPECT

Gurugrama is a town and municipal corporation in the Gurugram district of the state of Haryana, India. It is a part of the National Capital Region (NCR) of Delhi. Its proximity to the burgeoning city of Gurgaon has in recent years caused its character and demographics to change dramatically. It has many factories, offices, hotels, IT parks and educational institutes. There are several sightseeing spots around the area, some overlapping with Gurgaon

HORTICULURE IN RESPECT OF 4 ACRES OF COMMERCIAL COLONY AT VILLAGE WAZIRPUR, SEC-95A, GURUGRAM, HARYANA PROJECT REPORT/ESTIMATE FOR PROVIDING WATER SUPPLY, SEWERAGE, STROM WATER DRAINAGE, ROADS, STREET LIGHTING AND

95A, Gurugram, Haryana Developers Pvt Ltd. They have decided to develop the area in this master plan as a commercial colony for an area measuring 4 Acres at Village Wazirpur, Sector The Haryana Government has prepared a master plan for development of Commercial urban estate Gurugram. Project is doveloped by M/S Microtek Urban

Water Supply

Source

provisions of 10% stand by. Ultimately, water shall be supplied to the Project by HARYANA SHAHARI VIKAS PRADHIKARAN, GURUGRAM, HARYANA. worked out and the tubewells will be bored after the permission from CGWA in tune with growth of demand. The ultimate requirement of tubewells includes However still we shall resort to rain water harvesting system to keep up the recharging system. The number of tubewells required for the above area has been average yield of tubewell with 40-45 ft strainers will be about 10,000 litre per hour. The recharging of underground water table in this belt is stated to be good supply is from HSVP municipal supply and tanker supply is sweet and fit for human consumption. However in borewell water is available at reasonable depth. Thee The source of water supply in this area is from HSVP how ever tubewells shall be proposed for Emergency if permission will get from CGWA. At present water 7

ANOJ TEVATIA B. Arch (Hons)

2 <u>Design</u>

(45+15%) as per NBC 2016 / HSVP norms. The scheme has been designed for approved population of 4725 persons in 4 acres. The rate of water supply per head per day has been taken as 51.75 litres

3 Pumping Equipments

any electricity failure. Generator will be provided separately or added to the capacity of main generator. It has been proposed to install pumping set as described with standby of equal capacity. The provision for standby generating set has been provided in case of

4 Under Ground Storage

requirement. The water from fire compartment shall overflow to the raw water compartment so that the water in the fire compartment always remain fresh. Underground storage tank provision has been made for 250KL capacity. in 4 compartments, which caters for the raw, domestic as well as for firefighting

Boosting Station

Ġ

to over head water tank provided at individual plot terrace. A boosting station having monoblock centrifugal pump set is planned near under ground reservior to pump water from domestic/ treated under ground water tank

Distribution System

တ

Minimum pipe dia for distribution is kept as 100 mm dia for domestic water supply. The distribution system for this development has been designed to supply @ 51.75 litre per head her day @ 2.5 times the average rate of flow on 'Hazen william formula with C-140. Necessary provision for laying D.I. pipe K-7 conforming to relevent IS standards along with valves and specials has been made in the project The minimum terminal head at any point will be more than 30.00 meters so thet it can serve the stilt and four floors stories construction envisaged in the plan

Rising Mains

7

Rising mains from HSVP water main or sector road to water works have also been designed and provision for 100 mm dia D.I. pipe line (dia as/ design) has beer made in this estimate

Sewerage

œ

minimum velocity i.e. self cleansing velocity Necessary provision for laying DWC HDPE SN8 pipes and manholes etc. has been made in this estimate the propoesd sewer. DWC HDPE SN8 pipe sewers have been proposed and designed to run half full. The sewers have been designed on 0.75 M per second The sewer lines have been designed for 3 times average DWF in relation to the water supply demand assuming that 80% of water supply shall find its way into This scheme is designed for sewer connecting to the proposed sewage treatment plant. The sewage system has been marked on the respsctive plans

Size/ Shape of Manholes

manhole is proposed to be provided for depth upto 0.9m rectangular as well as arch type manholes. However both rectangular and circular type of manholes are propsed to be provided. The brick masonary rectangular As per IS 4111:1986 "Circular type of manholes are much stronger than rectangular and arch type manholes thus these type of manholes are preferred over

portion and slanting on top portion so as to narrow down the top opening equal to internal dia of manhole cover The brick masonry/ concrete circular manholes are proposed to be provided for all depth exceeding 0.9 m upwards. Circular manholes are strsaight down in lower

Depending on the depth of manhole, brick circular manhole of dia 910, 1220, 1520, 1820 mm dia are proposed to be provided

Storm Water Drainage

9

The storm water is designed to carry 6.25 mm rainfall per hour or 0.123 cusecs per acre, as discharge. Also suitable provisions are contemplated in our scheme to ensure better recarging of underground water table in the area. Underground R.C.C. pipe drain with minimum 400 mm dia are proposed to be provided in this area with circular manhole.

Necessary design statement for entire storm water system has been prepared and attached with estiamte

10 Rain Water Harvesting

water drainage system. Modular type rain water harvesting are proposed to be provided The main emphasis on recharging the underground aquifers and safe disposal of storm water with flooding the site has been laid in designing/ planning of storm

11 Roads

the basis of the detail design of the roads as approved by Chief Engineer HSVP, Gurugram. of the roads of the colony 6m wide provide approach for construction of roads to the plots. Detailed calculation of the various item of works have been made on The roads are proposed to be provided in the plotted development in such a way that main 6m wide colony road connects with 24 m sector road. Internal service

かななか

Street Lighting

2

road. Luminaries with 60 watts LED lights are proposed to be provided for achieving the desired illumination. Street lighting system has been designed to provide illumination of 15 to 20 lux on roads. Street lights are provided on 5 m high steel tubular poles are located on

13 Horticulture

tree guards. Provision of road side plantation of trees with tree guards has been made for all roads. The parks shall be developed by providing lawns & ornamental trees with

14 Specifications:

15

The work will be carried out in accordance with the standard sprcification of P.H. Department as laid down by HSVP & Haryana Government.

16 Cost

Estimate for providing services in this pocket has been prepared on the recent HSVP rates.

charges and 49% departmental charges also. The total cost of development in this project including various P.H. and B & R services works out to Rs. 554.83 Lacs which includes 3% contingency and PE

drainage, roads, street lighting and plantations including plantations maintenance thereof as well as future expansion whatsoever indicated The cost per gross acre for this phase works out to App. Rs. 138.71 Lacs/acre which covers the provision of services like water supply, sewerage, storm water

		lotal daily Water requirement for Staff (45 LPCD + 15%)	Total No. Staff	Staff per Shops	Total No. of Plots Shops	Total No. of Commercial Plots	Daily water requirement	DESIGN CALCULATION
		(9)						
26741.81	Domestic @ 65%	51.75	795 \	ω	265	53	Acres	For 4 Acres
14399.44	Flushing @ 35%	LPCD	Persons	Person/Shops	Nos	Nos		Unit
LPD								

	Oi	4		ω		Ν
	Area under Roads Daily water requirement Therefore daily water requirement	Area under Green (5% of Total area) Daily water requirement Therefore daily water requirement	All Total Water requirement (1 +2 +3)	Total Area of Upper floor Total No. of Person Total No. Person Floating Population (Total person- 3 PersonX Shops) Total daily Water requirement for Floating Population	Total No. Person Floating Population (Total person- 3 PersonX Shops) Total daily Water requirement for Floating Population (15 LPCD + 15%)	Total Area of Ground Floor Total No. of Person
Total	(2)	(2)	Or Say	(2)	(0)	s.
	1.92	0.20 25000	70886.93 50470.87 70.80 50.50	17624.591 6 2937 2301 17.25 557 Domestic @ 35% F	17.88 1629 17.25 Domestic @ 35% P. 245 16	5363.540
9.61	Acre lit/acre/day 9611 9.61	Acre lit/acre/day 5000	38/26.80 58467.69 38:50	sqm Sqm/Person Persons Persons LPCD Flushing @-65% 357.	Persons Persons LPCD Thushing @ 65% 9875.08 18263.44	sqm Sqm/Person
KLD	lit/day KLD	lit/day KLD	KLD		LPD \	

							=			b)	<u>a</u>	_	
		Add 10% standby	No. of tubewells required	Total domestic water requirment	Assuming discharge/hour of each tubewell	Assuming working hours of tubewells	Tubewell		Total Daily Requirement	Under Road+ Parks (4+5)	For (1+2+3)	Total daily requirement	
Proposed	Total							Or Say					
1.0	0.94	0.09	0.85	51	10)	6)		51.00	70.80	0.00	50.50	70.00	
Nos.	Nos.		Nos.	KLD	KL/hours	hours		74.00	52-73	\$2.73 \$6±73	58.50		28-12
								KLD	KLD ,	XLD XLD	KLD		

So It is proposed 1 nos of tubewell if permission will get from from CGWA. The provision of 1 no of tubewell has been made in the estimate because the water demand for flushing, horticulture and the road washing purpose is to be met from re circulated after treatment at STP and ultimate water supply is to be provided by HSVP.

					<u>a</u>	0	b)	a)	≡
It is proposed to install 1 no. Submersible pu	With 60% efficiency	BHP = $(20x1000x60)/(60x60x75x0.6)$	· ·		Friction loss	Depression head	Average Fall in S.L	Gross working load	Pumping machinery for tubewell
It is proposed to install 1 no. Submersible pumping set with a discharge of 10000 ltr./hour (167 lpm) driven with 5 HP electric motor.	Proposed	Ш	Say =	н	Ш	III	II	11	
(167 lpm) driven with 5 HP elec	5.00	3.70	60.00	56.65	2.50	6.10	3.05	45.00	
tric motor.	¥	픇	3	3	3	3	3	3	

Q () () (a)				V
It is proposed to provide under ground tank of following capacity Capacity of Fire tank-1 Capacity of Fire tank-2 Capacity of Raw Water tank Capacity of Domestic Water tank	I otal It is proposed to provide 1 no. under ground tank of capacity 45°KL for raw water, 1 no. underground underground tank of 110 KL each capacity for fire fighting. Tank will have four compartments, Two for fire, one for raw and one for domestic use. The water first water use compartment so that the water in the fire compartment shall remain fresh.	Fire Tank Capacity as 100 x [sqrt(4725) /1000]	Capacity of under ground tank storage except fire fighting @ 60% of Total water requirement / 100 fixed for the commercial area	Underground Tank Daily requirement for domestic use and other except fire fighting
capacity	capacity 4 ting. — or raw an	Say	Say	
	45"KL for raw water, 1 no. under the form of the form	H (1	11 11 11	IH
110.00 1 110.00 35 15.00 35	**************************************	217.38 220.00	30.30 70.80 30.00 7/.00 4725	70 :⊗° 59:50
5 5 5 5	KLD & KLD mpartment, t		KLD Person	Z Z D
	**************************************	\ \ \ .	3 sqm/person	٠,٠,٠

		<u>S</u>	€	<u>=</u>	=									<
Say		Residual head	Clear head	Friction loss in M <main &="" specials<="" th=""><th>Suction lifts</th><th>Head of pump</th><th></th><th></th><th>Discharge/hour</th><th>Assuming 6 hours running 1 pumps (with one standby)</th><th>Daily requirement for domestic use</th><th>Domestic Water Transfer Pump</th><th>UG. Tank</th><th>BOOSTING MACHINERY (Drinking water)</th></main>	Suction lifts	Head of pump			Discharge/hour	Assuming 6 hours running 1 pumps (with one standby)	Daily requirement for domestic use	Domestic Water Transfer Pump	UG. Tank	BOOSTING MACHINERY (Drinking water)
H	##	\$I	II	Ħ	Н		Or Say		11		Н			
35.0	35.0	10.0 >	15.0	5.0	5.0		140:00 / 9 /	140.28 196.66	8.42	7.83	50.50	70.80		
Э	3	3	3	3	33		LPM	LPM	XL/17		X-C			

-												1
			6		<u>a</u>	0	b)	<u>a</u>	≤			
	STP Capacity required at 5% extra margin	Sewage flow will be 80% of total load	Sewage Treatment Plant capacity Gross domestic + Flushing water requirement/day		Lighting	Tubewell	Flushing Water Transfer Pump	Domestic Water Transfer Pump	Gen Set		BHP of motor (140*35)/(60*75*0.6)	197
			ment/day	07.12.6 x 0.746 x 1.50 Say	1 2.1	1 5.0	1 3.0	1 2.5- 3: 20	Nos. HP			
					Ш	Ш	Ш	11	7	Or Say	II	
	91.56	87.2	109.0							35000	1.81	2-55
	KLD	KLD	KLD	14 14.65	2.1	5.0	3.0	2.5	277	퐈	품	
					∓	퓨	퓽	품			, //	

	₹	≦
Say μ 8 BHP of motor (240*35)/(60*75*0.6)	STP Daily requirement for Flushing & Horticulture use Assuming 6 hours running 1 pumps (with one standby) Discharge/hour Head of pump Suction lifts Friction loss in M <main &="" clear="" head="" head<="" residual="" specials="" td=""><td>STP Capacity (Or Say) STP Treated Tank Daily requirement for flushing, horticulture, road washing Capacity of under ground tank 60% of Total Water requirement S</td></main>	STP Capacity (Or Say) STP Treated Tank Daily requirement for flushing, horticulture, road washing Capacity of under ground tank 60% of Total Water requirement S
JH16-1 =		Say
		m 11 17
Or Say	Or Say	
	5.0	
∓ ∓ ∃ ∃	E PM FED FOR THE FOR T	5 5 5 5
)

FINAL ABSTRACT OF COST

Sub Work 1- Water Supply

Amount (Lacs.) For 4 Ac -93.00 //3./6

Sub Work 2- Sewerage

37.61 58.96

Sub Work 3- S.W. Drainage

25.93 48.09

Sub Work 4- Roads

473.43 2/3.89

Sub Work 5- Street Lighting

15.35 15.35

Sub Work 6- Horticulture

Sub Work 7- Maintenance of services for 10 years including resurfacing of roads after 1st 5 years & II. Phase i.e. 10 years maintenance (as per HSVP norms)

2.32 11.78

207.20 207.20

554.83 668.53 438.71 /67.13

COST / ACRE

668.53

Checked for service estimate only

Executive Engineer EDC (Infra-I) GMDA for roads/lighting/Hort.

Drainage Division, GMDA, Executive/Engineer-III Gurugram

> attached with the estimate Dt. 2 注 - 1.2 - 1.0 2 2 - and notes

in forwarding letter No.1./.5.334/2022

Checked subject to comments

(Infra-II), GMDA

sew. Division No. In GMDA, Gurugram

Executive Engineer-I W/S Division, GMDA

Gurugram

Gurugram

Haryana, Chandigarh

Director General Town & Country Planning

Page 11

(CO to final abstract of cost)	Add 49% Departmental Charges	Add 3% Contingencies & PE Charge	Total	Sub Head 4- Fire Fighting System	Sub Head 3- Distribution System	Sub Head 2- Pumping Machinery	Sub Head 1- Head Works	WATER SUPPLY HEAD
SAY	TOTAL							
-93.00 /13·16	93.27 113·16	1.82 2.2	60.74 73.74	12.12 /2.57	11.27 17.67	12.10	25.25 3/·40	Amount (Lacs.)

Sub Head I No. Description I Boring and installing 510 mm if tubewells with Population and Expense depth of about 80m. complete with pipe strainer to a depth of about 80m. complete with 90						
Boring and installing 510 mm i/d tubewells with Nos. Perverse/direct rotary rig complete with pipe strainer to a depth of about 80m. complete. Constructing pump chambers as per standard design of PWD PH/HQVP of size 1.50x1.50 m. Construction of boosting chambers of suitable size along with under ground tank pumping machinery and generating set etc. complete in all respects. Details of boosting chamber construction of boosting chamber construction of UG Tank Provision for carriage of material and other unforeseen LS tems Provision for facilities staff for Maintenance. LS LS	3/·40 26.25	SAY				
Description Description Description Unit Description Unit Description Unit Description Unit Description Unit Description Unit Description Light All L	3/.40	TOTAL			(C.O. to abstract of cost of Sub-work No.I)	
Description Description Description Description Unit Oty Rate Description Unit Description Unit Description Unit Description Unit Description It tubewells with Nos. 1 1000000.00 Publication of boosting chambers as per standard design of Publication of boosting chambers of suitable size along with under ground tank pumping machinery and generating set etc. complete in all respects. Details of boosting chamber construction of boosting chamber construction of UG Tank Provision for carriage of material and other unforeseen LS LS LS LS LS LS LS LS LS L	1.00	rs /		S	Provision for facilities staff for Maintenance.	Οī
Description Descr	\					
Description Descr	1.00	LS \		S	Provision for carriage of material and other unforeseen items	4
Description Unit Octy Rate Boring and installing 510 mm i/d tubewells with Nos. reverse/direct rotary rig complete with pipe strainer to a depth of about 80m. complete. Constructing pump chambers as per standard design of Nos. PWD PH/HSYP of size 1.50x1.50 m. Construction of boosting chambers of suitable size along with under ground tank pumping machinery and generating set etc. complete in all respects. Details of boosting chamber Unit Octy Rate 1 000000.00 1 1000000.00 1 1000000.00 1 1000000.00 1 100000.00 1 100000.00 1 100000.00 1 100000.00 1 10	17:40	4500.00	250	7	construction of UG Tank	ij
Description Unit Description Unit Oty Rate Boring and installing 510 mm i/d tubewells with Nos. reverse/direct rotary rig complete with pipe strainer to a depth of about 80m. complete. Constructing pump chambers as per standard design of PWD PH/HSVP of size 1.50x1.50 m. Construction of boosting chambers of suitable size along with under ground tank pumping machinery and generating set etc. complete in all respects. Details of boosting station	1.00	LS \	290		construction of boosting chamber	ij
Description Boring and installing 510 mm i/d tubewells with Nos. reverse/direct rotary rig complete with pipe strainer to a depth of about 80m. complete. Constructing pump chambers as per standard design of Nos. PWD PH/H6VP of size 1.50x1.50 m.	\				Construction of boosting chambers of suitable size along with under ground tank pumping machinery and generating set etc. complete in all respects. Details of boosting station	ω
Sub Head I Description Description Boring and installing 510 mm i/d tubewells with Nos. reverse/direct rotary rig complete with pipe strainer to a depth of about 80m. complete.	1.00	100000.00	_	Nos.	Constructing pump chambers as per standard design of PWD PH/HSVP of size 1.50x1.50 m.	2
	Amount	Rate 1000000.00	Qty 1	Unit Nos.	Description Boring and installing 510 mm i/d tubewells with reverse/direct rotary rig complete with pipe strainer to a depth of about 80m. complete.	S. No.
	Water Supply Head Works Rs.(lakhs)				Sub Head I	

	Sub Work I Sub Head No. II			a a	Water Supply Pumping Machinery Amount (Rs.) (in Lakhs)	lery
S. No.	Description	Unit	Qty	Rate		
_	Providing and installing electricity driven electro or submersible pumping set capable of delivering about 20 KL water per hour against a total head of 60 M complete with motor and other accessories.	Nos.)	200000.00	2.00	
ა	Drawing for about processing type obliganting plant				1 00	
1	complete.					
ω	Provision for making foundations & erection of pumping machinery.			5	0.50	
4	Provision for pipes, valves & specials inside the pump chamber.			5	0.50	
Ŋ	Provision for electric services connection including electric fittings for tubewells chambers complete. Including cost of trasfermer.			5	1.00	1
o	Providing and installing electricity driven pumping set, capable of delivering 140 LPM of water at 35M head complete in all respects. (2.5 HP) (Domestic Water					
	(1 working + 1 standby)	Nos.	2	110000.00	2.20	/

	9	∞	~
(C.O. to abstract of cost of Sub-work No.I)	Provision for carriage of materials and other unforeseen items.	Provision of diesel generator set of each for standby arrangements for booster pump complete with gear head arrangements of following capacities 15 KVA.	Providing and installing electricity driven pumping set, capable of delivering 210 LPM of water at 35M head complete in all respects. (3 HP) (Flushing Water Transfer Pump) (1 working + 1 standby)
			Nos.
			2
TOTAL	ſS	٣	120000.00
12.10 12.10	1.00	1.50	2,40
_	٩	1	<u> </u>

	Sub Work I Sub Head No. III				Water Supply Distribution System/Rising Main
S. No.	Description	Unit	Qty	Rate	IN LACS
_					2
i)	marked. (For Domestic water supply line) 100 mm dia	M	327	1250.00	4.09
Ν	Providing, laying, jointing & testing D.I. K-7 pipes including cost of excavation complete as per ISI				
i)	marked. (For borewell line) 100 mm dia	N. C.	15	1250.00	0.22
ω	Providing, laying, jointing & testing HDPE PE-80 pipes including cost of excavation complete as per ISI marked. (For Flushing water supply line)			147)	(3.4
i)	80-mm dia	M	326	800.00	2.61
4	Providing and fixing sluice valves including cost brick masonary chambers complete in all respects.			25000	
i)	100 mm i/d	Nos.	ట	12000.00	0.36
ഗ	Providing, fixing and testing butterfly valves including cost of valve chambers complete in all respects.				\
ij	80 mm i/d	Nos.	ω \	10000.00	0.30
თ	Providing and fixing 100 mm dia NRV including cost of valve chambers complete in all respects.				
i)	100 mmm dia	Nos.	_	14000.00	0.14
⋾	80 mmm dia	Nos.	_	10000.00	0.10

7 Providing and fixing air valves and scour valves Nos. 2 10000.00 0.20 including cost of valve chambers complete in all respects. 8 Providing and fixing indicating plates for sluice valve, Nos. 10 1000.00 0.10 1000.00 0.10 air valve etc. 9 Provision for carriage of material	100				
Providing and fixing air valves and scour valves Nos. Including cost of valve chambers complete in all respects. Providing and fixing indicating plates for sluice valve, Nos. Providing and fixing indicating plates for sluice valve, Nos. Including cost of valve chambers complete in all respects. Providing and fixing indicating plates for sluice valve, Nos. Including cost of valve chambers complete in all respects condition. Including cost of valve chambers complete in all respects condition. Including cost of valve chambers complete in all respects condition. Including cost of valve chambers complete in all respects condition. Including cost of valv	14.27	SAY			1
Providing and fixing air valves and scour valves Nos. Including cost of valve chambers complete in all respects. Providing and fixing indicating plates for sluice valve, Nos. In air valve etc. Provision for carriage of material Provision for cutting the roads and making to its original condition Making water supply connection 2 Commenters Provision for rising main from HSVP water supply line to UG Tank UG Tank M 15 1259.90	14.27/2-6	TOTAL		(C.O. to abstract of cost of Sub-work No.I)	
Providing and fixing air valves and scour valves Nos. including cost of valve chambers complete in all respects. Providing and fixing indicating plates for sluice valve, Nos. air valve etc. Provision for carriage of material Provision for cutting the roads and making to its original condition Making water supply connection 2 Composed LS Provision for rising main from HSVP water supply line to UG Tank 2 10000.00 10 1000.00 LS LS LS LS Provision for rising main from HSVP water supply line to	0.19		<	100 mm dia (DI Pipe K-7)	j
Providing and fixing air valves and scour valves Nos. including cost of valve chambers complete in all respects. Providing and fixing indicating plates for sluice valve, Nos. air valve etc. Provision for carriage of material Provision for cutting the roads and making to its original condition Making water supply connection 2 CommeMon LS LS LS		124	ie to		12
Providing and fixing air valves and scour valves Nos. 2 10000.00 including cost of valve chambers complete in all respects. Providing and fixing indicating plates for sluice valve, air valve etc. Provision for carriage of material Provision for cutting the roads and making to its original condition 2 1000.00 1000.00 10 1000.00 LS	45	LS	on Res	Making water supply connection 2 Come No	<u> </u>
Providing and fixing air valves and scour valves Nos. 2 10000.00 including cost of valve chambers complete in all respects. Providing and fixing indicating plates for sluice valve, Nos. air valve etc. Provision for carriage of material 2 1000.00 1000.00	1.00	LS	jinal		10
Providing and fixing air valves and scour valves Nos. 2 10000.00 including cost of valve chambers complete in all respects. Providing and fixing indicating plates for sluice valve, Nos. 10 1000.00 - air valve etc.	1.00	LS			9
Nos. 2 / 10000.00	0.10				∞
	0.20	^		Providing and fixing air valves and scour va including cost of valve chambers complete in respects.	7

(C.O. to abstr	3 Provision for c	3 Provision for MS complete	2 Providing & fi 45 M Head	1 Providing and complete with	S. No.	Sub Work I Sub Head No. IV
(C.O. to abstract of cost of Sub-work No.I)	Provision for carriage of material	MS Pipes, sluice valves, air valves	Providing & fixing of Diesel operated pump 2850 LPM 45 M Head	Providing and fixing 80 mmdia fire hydrant valve complete with brick masonry chamber .	Description	. IV
	S	ſ	Each	Each	Unit	
			>	ω	Qty	
TOTAL SAY	100000.00	500000.00	611622.00	15000.00	Rate	
12.72 12.12	1.00	5.00	6.12	0,450	IN LACS	Water Supply Fire Fighting Works

38.42	71						
2.31	1250.00	185	3		100 mm dia pipe	100	(i
2.73	1475			to HSVP main line	Provision for DI K-7 pipe from S.T.P. to HSVP main line (Over flow line)	Prov (Ove	7
75.2	2-5000.00	95	주	5 KL including civil ks. It also includes	Providing and installation of STP 95 KL including civil tanks and all electro mechanical works. It also includes flushing tank.	Prov tank: flush	<u></u>
1100	S	£	ion fee	sto come	Provision for connection with HSVP	Prov	5
1.00	S			arriage of materials	Provision for cutting of roads and carriage of materials etc. and other unforsean charges	Prov etc. :	4
1.00	LS				Provision for timbering & shoring	Prov	ω
1.00	LS			emporary diversion	Provision for lighting, watching and temporary diversion traffic	Provis traffic	2
3-137	2370	142	Ζ		Average depth 1.5 m to 4.5 m		b)
7.5-7	2270	69	≤		200 mm i/d Average depth upto 1.5 m		<u>a</u> =;
in Lacs	Rate	Qty	Unit	DWC HDPE SN8 including cost of holes complete.	Providing, lowering, jointing, cutting DWC HDPE SN8 pipes and specials into trenches including cost of excavation, bed concrete lot of manholes complete.		∴ No.
Sewerage Scheme					Sub Work II	Sub	

	(C.O. TO FINAL ABSTRACT OF COST SUB WORK - II)		Add 49% Deptt. Charges			Add 3% contingencies & PE charges	
	SAY	TOTAL					
58.96	<37.64	37.61 58. PG	1257	39.57	25.24	6.74	

0·28 0·28 1·28	2600 LS	10	ζ ≤	Provision for connection with HSVP. 400 mm i/d (Average depth 1.5 m to 4.5 m) Provision for connection with HSVP line	7 6
18.W	250000:00	*	Nos	Construction of rain water harvesting pit as per details and specification given below and as per attached drawing including, cost of excavation of all ind soil foundation trenches of drain including dressing of sides of ramming and getting out excavtion of soil.	O
1.00	LS			Provision for cutting of roads and carriage of materials etc. and other unforseen items.	4
1.00	LS			Provision for lighting, watching and temporary diversion of traffic.	ω
1.00	LS .			Provision for road gully and drain.	2
4.19 3.56 1.58	2500.00 2500.00	142 61	≤ ≤	400 mm i/d Average depth upto 1.5 m Average depth 1.5 m to 4.5 m	<u>p</u> <u>a</u> =
In Lacs	Rate	Qty	Unit	Description Providing, lowering, jointing, cutting RCC NP2 pipes and specials into trenches including cost of excavation cost of manholes, ventilating chambers etc. complete in all respects.	S. No.
Storm water drainage		*		Sub Work III	

	(C.O. TO FINAL ABSTRACT OF COST SUB WORK - III) SAY	Add 49% Deptt. Charges		Add 3% contingencies	
60.84	25.93 48709 25.93	8.53~ (5-8)	47:40 32,28	0:54 0.90	46.90-37.49

თ	ហ	4	(b)	a a		2	_	S. No.	
Provision for plot indicator	Provision for carriage of material	Provision for traffic lighting and guide map	Provision of foot path of precast conc. for 4 acres 560 x 1.5 = 840 SQM	Miscellaneous items Providing for Kerbs & Channels for 4 acres Bounday side 560 x 1 = 1107 RM	ii) Providing GSB by 250 mm thick +2,70 mm W MM ii) 150 mm thick P.C.C. (1:4:8) iii) 40 mm Sand. + 70 mm B M + iv) 80 mm Pavers. Yo mm B Total	Construction of road by-	Provision for levelling and earth filling as per site conditions.	S. No. Description	Sub Work IV
LS	LS	LS	Sq. M	RMT	Sq. M		Acre	Unit	
			840	560	7778.65		4	Qty	
100000.00	100000.00	100000.00	750:00	600.00	750.00		177 200 .00	Rate	
1.00	1.00	1.00	8:40	3.36	93.34		67.00	in Lacs	Road Work

(C.O. TO FINAL ABSTRACT OF COST SUB WORK - IV)	Add 49% Deptt. Charges	Add 3% contingencies	7 Provision for demaracation & unfloreseen items LS
TOTAL SAY			100000.00
773.43 213-99 473.43 213-99	57.03 70·37	3.39 4.18	1.00

15.35	SAY	d i	(C.O. TO FINAL ABSTRACT OF COST SUB WORK - V)
15.35	TOTAL		
5.05			Add 49% Deptt. Charges
10.00 0.30			Add 3% contingencies
10.00	250000.00	L.S. 4	all respect Provision made on L.S. cost @ Rs.2,50,000.00 per acre
In Lacs	Rate	Unit Qty	S. No. Description 1 Providing street lighting on internal roads as per
Street Lighting			Sub Work V

						2	0	b)	<u>a</u>	_	S. No.	
(C.O. TO FINAL ABSTRACT OF COST SUB WORK - VI)		Add 49% Deptt. Charges	Add 3% contingencies	Cost of the tree @ 13007- each	Total length of side = 560 mtr No of trees @ $12 \text{m c/c} = 560 \text{x} 2/12 = 93 \text{ nos}$		Grassing with including watering and maintenance of Per acre lawns free from weds and fit for moving in rows including for hedges, shrubs and green belt (as per HSVP Norms)		Trenching the ordinary soil upto depth of 60 cm. including removal and apcking of servicable material and disposing at the lead of 50m and making upto the tranched area to prope level by filling with earth mixed with manure before and after flooding trenches with water including cost of imported earth and manure.	Development of lawn area	lo. Description	Sub Work VI
1)				Nos.							Unit	
				93			0.20	1			Qty	
SAY	TOTAL			4300.00)		150000.00				Rate	
232	-2.32 11-78	1.55 7.91	0.05 20.05	1.68	7		0.30	6.00		In Lacs	Amount	Horticulture

				ω	N	S. No	
(C.O. TO FINAL ABSTRACT OF COST SUB WORK - VII)		Add 49% Deptt. Charges	Add 3% contingencies	Provision for resurfacing and strengthening of road after 10 years of 2nd phase with 80 mm paver block @ 750/sqm	Provision for resurfacing and strengthening of roads after 1st five years of 1st phase with 80 mm thick paver block @600/sqm	S. No. Description 1 Provision for maintenance charges for water supply, sewerage, storm water drainage, roads, street light, horticulture etc. complete including operation and establishment charges as per HSVP norms after completion and resurfacing of roads after 10 years or 1st phase.	Sih Work VII
				Sq.	Sq. M	Unit Acre	
				7778.645	7778.645	Qty 4	
SAY	TOTAL			750.00	600.00	Rate 750000.00	
207.20	207.20	139.06 68.14 68.14	135.01 — 4.05 —	58.34	46.67	in Lacs 30.00	Maintenance

				ယ	N	S. No.	
(C.O. TO FINAL ABSTRACT OF COST SUB WORK - VII)		Add 49% Deptt. Charges	Add 3% contingencies	Provision for resurfacing and strengthening of road after 10 years of 2nd phase with 80 mm paver block @ 750/sqm	Provision for resurfacing and strengthening of roads after 1st five years of 1st phase with 80 mm thick paver block @600/sqm	S. No. Description 1 Provision for maintenance charges for water supply, sewerage, storm water drainage, roads, street light, horticulture etc. complete including operation and establishment charges as per HSVP norms after completion and resurfacing of roads after 10 years or 1st phase.	Sub Work VII
				Sq. M	Sq. M	Unit Acre	
				7778.645	7778.645	Qty 4	
SAY	TOTAL			750.00	600.00	Rate 750000.00	
207.20	207.20	139.06 S	135.01 \(\) 4.05 \(\)	58.34	46.67	in Lacs 30.00	Maintenance

Á.