



TYPE	WIDTH	CILL	LINTEL
FD	1200	0.00	2400
ONE HOUR FIRE RATED DOOR			
D1	1200	0.00	2400
D2	1200	0.00	2400
D3	800	0.00	2400
D4	750	0.00	2400
D5	700	0.00	2400
SD	1000	0.00	2100
SLD1	2750	0.00	6600
SLD1A	2750	0.00	2400
SLD2	2750	0.00	2400
SLD3	1875	0.00	1900
SLD4	1820	0.00	2400
SLD4	2400	0.00	2400
SLD5	1500	0.00	2400
DW1	900	0.00	1050
DW2	900	0.00	1050
DW3	1200	0.00	2400
W	900	0.00	900
LOVERED WINDOW IN STAIRCASE			
W1	1500	1200	2400
W2	900	1050	2400
W3	1200	900	2400
W4	1700	900	2400
W5	1350	1350	2400
V1	600	1200	2400
V2	600	750	2400
V3	450	1200	2400

NOTE:- 1. ALL MAIN UNIT ENTRY DOOR WILL BE ONE HOUR FIRE RATED DOOR
2. ALL SHAFTS (FHC, ELECTRICAL & LV) DOOR WILL BE FIRE DOOR.
3 STAIRCASE WILL HAVE LOUVERED WINDOW



PENT HOUSE (Upper lvl) AT 30th FLOOR LVL






DTP (HQ) S.T.P (HQ) S.T.P (G) Member Chairman
 Member Secretary Member B.P.A.C. B.P.A.C.





High No
 Consultant Architect
 P1
 ATP (HQ)

Checked and found ok for Public Health
 (Internal) Service only subject to comments in
 forwarding letter No. 1.53.825.DU.14/2/27

