STATE ENVIRONMENT IMPACT ASSESSMENT AUTHORITY HARYANA Bay No. 55-58, Prayatan Bhawan, Sector-2, PANCHKULA.

No. SEIAA/HR/2019/496

Dated: 20-12-2019

To

M/s S. A. Propcon in collaboration with M/s Signature Infrabuild Pvt. Ltd. 1309, 13th floor, Dr. Gopal Das Bhawan, 28, Barakhamba Road, New Delhi-110001.

Environment Clearance for Affordable Group Housing Colony Project Village Dhorka, Sector 95, Gurugram, Haryana.

 \equiv received on 21.08.2019 seeking prior Environmental Clearance for the above project under the meeting held on 16.09.2019 awarded "Gold" rating / grading to the project. (SEAC) constituted by MoEF & CC, GoI vide their Notification dated 30.01.2019, in its clarifications furnished in response to the observations of the State Expert Appraisal Committee enclosed with the application viz., Form-1, Form1-A, Conceptual Plan and additional light of provisions under the EIA Notification, 2006 on the basis of the mandatory documents EIA Notification, 2006. The proposal has been appraised as per prescribed procedure in the This letter is in reference to your application addressed to M.S. SEIAA, Haryana

given below: Colony Project Village Dhorka, Sector 95, Gurugram, Haryana. The details of the project as It is inter-alia, noted that the project involves the Affordable Group Housing

Sr. No.	
	Gross Plot Area
2.	Proposed FAR
ω.	Non FAR Area
4.	Proposed Green Area
5.	Total Built Up Area
6.	Proposed Ground Coverage
7.	Total Population
.∞	Total Water Requirement
9.	Domestic Water
10.	Fresh Water
11	Treated Water
12.	Waste Water Generation
13.	Capacity of STP
14.	RWH Pits
15.	Parking (ECS)
16.	Solid Waste
17.	OWC
18.	Power Requirement
19.	No. of Buildings
20.	Max.no of floors
21.	Dwelling units
22.	Height of the building
23.	Anganwadi
24.	No. of DG Sets
25.	Cost of the Project
26.	CER
26	Incremental Load in i)PM 2.5

respect of ii) PM₁₀ 0.008 µg/m

with the following stipulations mentioned below: project under Category 8(a) of EIA Notification 2006 subject to the strict compliance with the to agree with the recommendations of SEAC to accord necessary environmental clearance for the State Environment Impact Assessment Authority in its 121st meeting held on 25.11.2019 decided project mentioned above, subject to compliance with the stipulated conditions. Accordingly, the response to its observations, have recommended the grant of environmental clearance for the relevant documents submitted by the project proponent and additional clarification furnished in 3 The State Expert Appraisal Committee, Haryana after due consideration of the

Specific Conditions:-

- Sewage shall be treated in the STP based on MBR Technology with tertiary treatment i.e. Ultra Filtration. The Treated effluent from STP shall be recycled /reused for flushing. DG cooling and Gardening.
- 2 Wildlife Warden, Haryana before the start of the project. The project proponent shall get approve the conservation plan from Chief
- ယ technical support from The PP shall restore, reclaim and maintain the ponds in villages Dhorka with the Haryana Pond and Waste Water Management
- 4 water being used for flushing in terms of faecal coli forms and other pathogenic The Project Proponent would devise a monitoring plan to the satisfaction of the State Pollution Control Board so as to continuously monitor the treated waste
- S supplied for flushing (specially the bacterial counts), comparative bacteriological toilet seats. studies from toilet seats using recycled treated waters and fresh waters for flushing, and quality of water being supplied through spray faucets attached to implementation of conditions related to quality and quantity of recycle and reuse of treated water, efficiency of treatment systems, quality of treated water being would commission a third party
- 7 6 Separate wet and dry bins must be provided in each unit and at ground level for facilitating segregation of waste. Solid Waste shall be segregated into wet garbage and inert materials. Wet Garbage shall be composted in Organic waste convertor. Adequate area shall be provided for solid waste management within the premises which will include area for segregation, composting. The Inert waste from the
- Traffic management plan as submitted shall be implemented in letter and spirit. Apart, a detailed traffic management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is marinated and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habilitation being carried out or purpose to be carried out by the project or other agencies in this 05kms radius of the site in different scenarios of space and time
- ∞ No tree cutting has been proposed in the instant project. A minimum of 1 tree for every 80sqm of land should be planted and maintained. The Existing trees will be counted for this purpose. The landscape planning should include plantation of native species. The species with heavy foliage, broad leaves and wide canopy cover are desirable. Water intensive and/or invasive species should not be used for landscaping. As proposed 4948.673 sqm(23.92%) shall be provided for green area development.
- 9 The Project Proponent shall obtain all necessary clearance/permission from all relevant agencies including town planning authority before commencement of

- byelaws. work. All the construction shall be done in accordance with the local building
- 10. Consent to establish/operate for the project shall be obtained from the State Pollution Control Board as required under the Air (Prevention and Control of pollution) Act, 1981 and the Water (Prevention and control of pollution) Act,
- 11. The PP shall submit the documents for final approval of 12% extra FAR from the concerned authority before the start of the project.
- 12. of building code due to earthquakes, adequacy of firefighting equipments etc. as per National Building Code including protection measures from lightening etc. The project proponent shall comply with the provisions contained in Ministry's OM vide F.No. 22-65/2017-IA.III dated 1st May 2018, as applicable, regarding The Approval of the Competent Authority shall be obtained for structural safety
- 13 Corporate Environment Responsibility.
- 14 The PP shall not give occupation or possession before the water supply and sewage connection permitted by the competent authority.
- 15 The PP shall not give occupation or possession before the electricity connection
- 16 permitted by the competent Authority.

 The PP shall obtain the permission regarding withdrawal of ground water from CGWA before the start of the project and also obtained the CTO from HSPCB after the approval from CGWA.
- 17. the commercial colony/project. The PP shall carry out the quarterly awareness programs for the stakeholders of
- 18 CGWB norms. 06 Rain Water Harvesting Pits shall be provided for rainwater usages as per the
- 19 The PP shall install Digital water level recorder for monitoring the water recharge
- 20 and carry out quarterly maintenance and cleaning of 06 RWH pits.

 The PP shall carry out various wildlife conservation activities like artificial nests on the trees, digging of ponds, construction of feeding platforms through on the trees, digging of pon Environment Management Plan.
- 21 22
- dust during construction and operational phase.

 Any change in stipulations of EC will lead to Environment Clearance void-ab-The PP shall provide the mechanical ladder for use in case of emergency.

 The PP shall take all preventive measures including water sprinkles to control
- 23. initio and PP will have to seek fresh Environment Clearance.

₽. Statutory compliance:

- The project proponent shall obtain all necessary clearance/ permission from all relevant agencies including town planning authority for ground coverage, FAR and should be in accordance with zoning plan approved by Competent Authority before commencement of work. All the construction shall be done in accordance
- [2]with the local building byelaws.

 The approval of the Competent Authority shall be obtained for structural safety of National Building Code including protection measures from lightening etc due to earthquakes, adequacy of firefighting equipment etc as per
- [3]The project proponent shall obtain forest clearance under the provisions of Forest (Conservation) Act, 1986, in case of the diversion of forest land for non-forest purpose involved in the project.
- 4 Wildlife, if applicable. project proponent shall obtain clearance from the National Board for
- [5] The project proponent shall obtain Consent to Establish/Operate under the provisions of Air (Prevention & Control of Pollution) Act, 1981 and the Water (Prevention & Control of Pollution) Act, 1974 from the Haryana State Pollution Control Board
- [6] The project proponent shall obtain the necessary permission for drawl of ground water /surface water required for the project from the competent authority.
- [7] A certificate of adequacy of available power from the agency supplying power to
- $[\infty]$ the project along with the load allowed for the project should be obtained. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department shall

authorities be obtained, as applicable, by project proponents from the respective competent

[9] shall be followed. (Management) Rules, 2016, and the Plastics Waste (Management) Rules, 2016 The provisions of the Solid Waste (Management) Rules,

[10]The project proponent shall follow the ECBC Act/ECBC-Rules prescribed by Bureau of Energy Efficiency, Ministry of Power strictly in addition of bylaws of the State Government.

Ë Air quality monitoring and preservation

- Implementation of Dust Mitigation Measures for Construction and Demol. Activities for projects requiring Environmental Clearance shall be complied with. A management plan shall be drawn up and implemented to contain the cu 94(E) dated 25.01.2018 of MoEF&CC regarding Mandatory Mitigation Measures for Construction and Demolition
- **:**: exceedance in ambient air quality at the site. contain the current
- Ħ: monitoring for common/criterion parameters relevant to the main pollutants released (e.g. PM10 and PM25) covering upwind and downwind directions during the construction period project proponent shall install system to carryout Ambient Air
- <u>1</u>V. Diesel power generating sets proposed as source of backup power should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use of ultra low sulphur diesel. The location of the DG sets may be decided with in consultation with State Pollution Control Board
- ۷. smoke & other air pollution prevention measures shall be provided for the building as well as the site. These measures shall include screens for the building under Construction site shall be adequately barricaded before the construction begins. Dust construction, continuous dust/ wind breaking walls all around the site (at least 3 meter height). Plastic/tarpaulin sheet covers shall be provided for vehicles bringing in sand, cement, murram and other construction materials prone to causing dust pollution at the site as well as taking out debris from the site.
- <u>√</u>1. Sand, murram, loose soil, cement, stored on site shall be covered adequately so as to
- prevent dust pollution.
- VIII. V11. Wet jet shall be provided for grinding and stone cutting.
 Unpaved surfaces and loose soil shall be adequately sprinkled with water to suppress
- 1×. the roads or open spaces outside) before they are properly disposed. All demolition and construction waste shall be managed as per the provisions of the Construction and Demolition Waste Rules 2016. All construction and demolition debris shall be stored at the site (and not dumped on
- × sulphur diesel type and shall conform to Environmental (Protection) prescribed for air The diesel generator sets to be used during construction phase shall be ultra low and noise emission standards
- X. The gaseous emissions from DG set shall be dispersed through adequate stack height as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution. Ultra low sulphur diesel shall be used. The location of the DG set and exhaust pipe height shall be as per the provisions of the Central Pollution Control Board (CPCB) norms.
- X11. For indoor air quality the ventilation provisions as per National Building Code of

I. Water quality monitoring and preservation

- ٠. sustainable urban drainage systems (SUDS) are allowed for maintaining the The natural drain system should be maintained for ensuring unrestricted flow of pattern and to harvest rain water r. No construction shall be allowed to obstruct the natural drainage through the on wetland and water bodies. Check dams, bio-swales, landscape, and other
- ≓: Buildings shall be designed to follow the natural topography Minimum cutting and filling should be done. as much as possible

- Ħ. Total fresh water use shall not exceed the proposed requirement as provided in the project details. The per capita supply should adhere to NBC 2016 and CGWA Notification dated 12.12.2018.
- Į. < measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along The quantity of fresh water usage, water recycling and rainwater harvesting shall be A certificate shall be obtained from the local body supplying water, with six monthly Monitoring reports.
- ⊴. total annual water availability with the local authority, the quantity of water already committed, the quantity of water allotted to the project under consideration and the balance water available. This should be specified separately for ground water and surface water sources, ensuring that there is no impact on other users. At least 20% of the open spaces as required by the local building bye-laws shall be
- would be considered as pervious surface pervious. Use of Grass pavers, paver blocks with at least 50% opening, landscape etc.
- V11. car washing, thermal cooling, conditioning etc. shall be done.
 Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow bathing etc and other for supply of recycled water for flushing, landscape irrigation, Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and
- VIII. plan. faucets tap aerators etc) for water conservation shall be incorporated in the building
- X. giving dual plumbing system be done. Water demand during construction sh system. of grey and black water should be done by the use of dual plumbing case of single stack system separate recirculation lines for flushing by
- × demand during construction should be reduced by use of pre-mixed concrete
- X. curing agents and other best practices referred.

 The local bye-law provisions on rain water harvesting should be followed. If local byelaw provision is not available, adequate provision for storage and recharge should be followed as per the Ministry of Urban Development Model Building Byelaws, 2016. The Rain Water Harvesting storage tanks shall be provided for ground water recharging as per the CGWB norms.
- X11. capacity of minimum one day of total fresh water requirement shall be provided. In areas where ground water recharge is not feasible, the rain water should be harvested and stored for reuse. The ground water shall not be withdrawn without approval from the Competent Authority. minimum one recharge A rain water harvesting plan needs to be designed where the recharge bores of bore per 5,000 square meters of built up area and storage
- XIII. All recharge should be limited to shallow aquifer.
- XV. No ground water shall be used during construction phase of the project. Any ground water dewatering should be properly managed and shall conform to the approvals and the guidelines of the CGWA in the matter. Formal approval shall be taken from the CGWA for any ground water abstraction or dewatering.
- XVI. The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
- XVII. Sewage shall be treated in the STP with tertiary treatment. The treated effluent from STP shall be recycled/re-used for flushing, AC make up water and gardening. As proposed, no treated water shall be disposed in to municipal drain.

 No sewage or untreated effluent water would be discharged through storm water
- XVIII
- XIX installation of the Sewage Treatment Plant (STP) shall be certified by an independent expert and a report in this regard shall be submitted to the Ministry before the project is commissioned for operation. Treated waste water shall be reused on site for landscape, flushing, cooling tower, and other end-uses. Excess treated wa discharged as per statutory norms notified by Ministry of Environment, Onsite sewage treatment of capacity of treating 100% waste water to be installed. The Climate Change. Natural treatment systems shall be promoted reated waste water shall be reused on site for and other end-uses. Excess treated water shall be
- XX Periodical monitoring of water quality of treated sewage shall be conducted
- Necessary measures should be made to mitigate the odour problem from STP. Sludge from the onsite sewage treatment, including septic tanks, shall be collected, conveyed and disposed as per the Ministry of Urban Development, Central Public

Health and Environmental Engineering Org Sewerage and Sewage Treatment Systems, 2013. Organization (CPHEEO) Manual on

II. Noise monitoring and prevention

- <u>.</u> day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality shall be closely monitored during construction phase. Adequate measures shall be made to reduce Ambient noise levels shall conform to residential area/commercial area both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. stipulated standards by CPCB / SPCB. ambient air and noise level during construction phase, so as to conform to the
- Ξ Noise Noise level survey shall be carried as per the prescribed guidelines and report in this regard shall be submitted to Regional Officer of the Ministry as a part of six-monthly compliance report.
- iii) Acoustic enclosures for DG sets, noise barriers for ground-run bays, ear plugs for due to ground sources. operating personnel shall be implemented as mitigation measures for noise impact

IV. **Energy Conservation measures**

- ۲. Compliance with the Energy Conservation Building Code (ECBC) of Bureau of Energy Efficiency as per ECBC Act, 2017 read with ECBC Rules, 2018 shall be ensured. Buildings in the States which have notified their own ECBC, shall comply with the State ECBC also which is in no case should be less than 25% as prescribed. Outdoor and common area lighting shall be LED.

 Concept of passive solar design that minimize energy consumption in buildings by
- **#**: #: envelope, appropriate fenestration, increased day lighting design and thermal mass etc. shall be incorporated in the building design. Wall, window, and roof R & Uvalues shall be as per ECBC specifications. using design elements, such as building orientation, landscaping, efficient building
- 1v. outside the building should be integral part of the project design and should be in place before project commissioning. Energy conservation measures like installation of CFLs/ LED for the lighting the area
- < generation equivalent to 1% of the demand load or as per the state level/ local wind or other Renewable Energy shall be installed to meet electricity
- ⊴. shall be provided to meet 20% of the hot water demand of the commercial and institutional building or as per the requirement of the local building bye-laws, whichever is higher. Residential buildings are also recommended to meet its hot water demand from solar water heaters, as far as possible. building bye-laws requirement, whichever is higher. Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power. Solar water heating
- ¥i: requirement and submit quantification saving report for each component. The PP will submit report indicating compliance of each parameter of ECBC

. Waste Management

- <u>..</u>. A certificate from the competent authority handling municipal solid wastes, indicating the existing civic capacities of handling and their adequacy to cater to the M.S.W. generated from project shall be obtained.
- **=**: general safety and health aspects of people, only in approved sites with the approval neighboring communities and be Disposal of muck during construction phase shall not create any adverse effect on the disposed taking the necessary precautions for
- Ξ: of competent authority.

 Separate wet and dry bins must be provided in each unit and at the ground level for facilitating segregation of waste. Solid waste shall be segregated into wet garbage and
- <u>۲</u> inert materials.

 Organic Waste Converter within the premises with a minimum capacity of 0.5 kg/person/day must be installed. Leaves to be put in earmarked pits for converting them into compost to be used as manure
- All non-biodegradable waste shall be handed over to authorized recyclers for which a

written tie up must be done with the authorized recyclers.

- ĭ. Any hazardous waste generated during construction phase, shall be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
- VII. materials, shall be required for at least 20% of the construction material quantity. These include Fly Ash bricks, hollow bricks, AACs, Fly Ash Lime Gypsum blocks, Compressed earth blocks, and other environment friendly materials. Use of environment friendly materials in bricks, blocks and other construction
- VIII. Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27th August, 2003 and
- Χ. Any wastes , 2016.Ready mixed concrete must be used in building construction. from construction and demolition activities related thereto sha
- × as per the prevailing guidelines/ rules of the regulatory authority to avoid mercury managed so as to strictly conform to the Construction and Demolition Rules, 2016. Used CFLs and TFLs should be properly collected and disposed off/sent for recycling contamination.

VI. Green Cover

- H No tree can be felled/transplant unless exigencies demand. Where absolutely necessary, tree felling shall be with prior permission from the concerned regulatory authority. Old trees should be retained based on girth and age regulations as may be species (planted). prescribed by the Forest Department. Plantations to be ensured species (cut) to
- Ξ_{i}^{*} species should not be used for landscaping. planning should include plantation of native species. The species with heavy foliage, broad leaves and wide canopy cover are desirable. Water intensive and/or invasive maintained. The existing trees will be counted for this purpose. The landscape A minimum of 1 tree (5' tall) for every 80 sqm of land should be planted and
- Ħ: Authority, compensatory plantation in the ratio of 1:10 (i.e. planting of 10 trees for every 1 tree that is cut) shall be done and maintained. Plantations to be ensured as per the details provided in the project document. species (cut) to species (planted). Area for green belt development shall be provided Where the trees need to be cut with prior permission from the concerned local
- VI Topsoil should be stripped to a depth of 20 cm from the areas proposed for buildings, roads, paved areas, and external services. It should be stockpiled appropriately in designated areas and reapplied during plantation of the proposed vegetation on site.

VII. Transport

- -8A comprehensive mobility plan, as per MoUD best practices guidelines (URDPFI), shall be prepared to include motorized, non-motorized, public, and private networks. The road system can be designed with these basic criteria.

 a. Hierarchy of roads with proper segregation of vehicular and pedestrian Road should be designed with due consideration for environment, and safety of users

- Traffic calming measures
- Proper design of entry and exit points. Parking norms as per local regulation.
- μ: applicable air and noise emission standards be operated only during non-peak hours. A detailed traffic management and traffic decongestion plan shall be drawn up to condition and should have a pollution check certificate and should conform to Vehicles hired for bringing construction material to the site should be in good
- H. and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. Development department and the P.W.D./ competent authority for road augmentation habitation being carried out or proposed to be carried out by the project or other agencies in this 05 Kms radius of the site in different scenarios of space and time and project is maintained and improved upon after the implementation of the project. This ensure that the current level of service of the roads within a 05 kms radius of the the traffic management plan shall be duly validated and certified by the State Urban plan should be based on cumulative impact of all development and increased drawn up to

VIII. Human health issues

- All workers working at the construction site and involved in loading, unloading, carriage of construction material and construction debris or working in any area with dust pollution shall be provided with dust mask.

 For indoor air quality the ventilation provisions as per National Building Code of
- **=**:
- 111. Emergency preparedness plan based on the Hazard identification Assessment (HIRA) and Disaster Management Plan shall be implemented. Hazard and Risk
- iv. necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project. Provision shall be made for the housing of construction labour within the site with all
- Occupational health surveillance of the workers shall be done on a regular basis.
- ≦. < operations of the project. A First Aid Room shall be provided in the project both during construction and

X. Corporate Environment Responsibility

- ۳. The project proponent shall comply with the provisions contained in this Ministry's OM vide F.No. 22-65/2017-IA.III dated 1st May 2018, as applicable, regarding Corporate Environment Responsibility.
- **:**: conditions. The company shall have defined system of reporting infringements/ deviation/ violation of the environmental/ forest/ wildlife norms/ conditions and/ or shareholders/ stake holders. The copy of the board resolution in this regard shall be submitted to the MoEF&CC as a part of six-monthly report. The company shall have a well laid down environmental policy duly approved by the Board of Directors. The environmental policy should prescribe for standard operating procedures to have proper checks and balances and to bring into focus any infringements/ deviation/ violation of the environmental/ forest/ wildlife norms/
- Ξ: A separate Environmental Cell both at the project and company head quarter level, with qualified personnel shall be set up under the control of senior Executive, who will directly to the head of the organization.
- īv. measures shall be kept in separate account and not to be diverted for any other purpose. Year wise progress of implementation of action plan shall be reported to the Ministry/Regional Office along with the Six Monthly Compliance Report. responsibility matrix of the company shall be prepared and shall be duly approved by implementing EMP and environmental conditions along with

× Miscellaneous

- The project proponent shall prominently advertise it at least in two local newspapers of the District or State, of which one shall be in the vernacular language within seven days indicating that the project has been accorded environment clearance and the details of MoEFCC/SEIAA website where it is displayed.
- **:**: to the relevant offices of the Government who in turn has to display the same for 30 proponents to the Heads of local bodies, Panchayats and Municipal Bodies in addition days from the date of receipt of the environmental clearance shall be submitted by the project
- E: The project proponent shall upload the status of compliance of the supulation environment clearance conditions, including results of monitored data on their website and update the same on half-yearly basis. shall upload the status of compliance of the stipulated
- V. compliance of the stipulated environmental conditions on the website of the ministry The of Environment, Forest and Climate Change at environment clearance portal. project proponent shall submit six-monthly reports on the
- < The project proponent shall submit the environmental statement for each financial year in Form-V to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently and put on the

- <u>⊻</u>. The project proponent shall inform the Regional Office as well as the Ministry, the date of financial closure and final approval of the project by the concerned authorities, commencing the land development work and start of production operation
- V11.
- VIII. The project authorities must strictly adhere to the stipulations made by the State Pollution Control Board and the State Government.

 The project proponent shall abide by all the commitments and recommendations made in the form-IA, Conceptual Plan and also that during their presentation to the Expert Appraisal Committee
- X. No further expansion or modifications in the plan shall be carried out without prior approval of the Ministry of Environment, Forests and Climate Change of area of this project. environmental clearance under EIA notification 2006 if at any stage there is change (MoEF&CC)/SEIAA, Haryana. of Environment, I proponent shall seek
- × Clearance to SEIAA. your ownership and possession of land legal the case referred for Environment The PP should give unambiguous affidavit giving land promoters in accordance with
- ≱. Environment (Protection) Act, 1986. Concealing factual data or submission of false/fabricated data may result in revocation of this environmental clearance and attract action under the provisions of
- XI: The Ministry/SEIAA may revoke or suspend the clearance, if implementation of any
- X111. of the above conditions is not satisfactory. The Ministry/SEIAA reserves the right necessary. The Company in a time bound manner shall implement these conditions Ministry/SEIAA reserves the right to stipulate additional conditions if found
- XIV. conditions. The project authorities should extend full cooperation to the officer (s) of the Regional Office by furnishing the requisite data / information/monitoring reports. The above conditions shall be enforced, inter-alia under the provisions of the Water The Regional Office of this Ministry shall monitor compliance of the stipulated
- VΧ Pollution) Act, 1981, the Environment (Protection) Act, 1986, Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016 and the Public Liability Insurance Act, 1991 along with their amendments and Rules and any other orders passed by the Hon'ble Supreme Court of India / High Courts and any other (Prevention & Control of Pollution) Act, 1974, the Air (Prevention & Control of
- XVI. Court of Law relating to the subject matter.

 The Project Proponent shall ensure the c environmentally friendly commitment on the point shall be taken as commitment by spirit. In case of contradiction between two or more documents on any point, the most environment and proposed environmental safeguards are complied with in letter and EIA/EMP and other documents submitted to the SEIAA for the protection of commitments made in Form-1, Form-1A
- XVII. any Court/Tribunal. project proponent. The Project proponent shall not violate any judicial orders/pronouncements issued by
- xviii. has been started before obtaining prior Environmental Clearance. Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the Project Proponent if it was found that construction of the project
- xix. Green Tribunal, if preferred, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010. Any appeal against the this Environmental Clearance shall lie with the National
- XX. The project proponent shall ensure the compliance of Forest Department, Haryana Notification no. S.O.121/PA2/1900/S.4/97 dated 28.11.1997.
- XXI. The project proponent is responsible for compliance of all conditions in Environmental Clearance letter and project proponent can not absolve himself/herself of the responsibility by shifting it to any contractor engaged by project proponent. been granted by the Town & Country Planning Department, Haryana Environmental Safeguards/ conditions imposed in the Environmental Clearance letter shall also lie on the licensee/licensees in whose name/names the license/CLU has Besides the developer/applicant, the responsibility to ensure the compliance of
- xxii.
- xxiii. The project proponent shall seek fresh Environmental clearance if at any stage there is change in the planning of the proposed project.

 The Project Proponent shall not raise any construction in the natural land depression / Nallah/water course and shall ensure that the natural flow from the Nallah/water course is not obstructed.

- XXIV. Projects shall also be kept suitably so as to avoid flooding. The project proponent shall construct a sedimentation ba above the level of the approach road to the Project. Levels of the other areas in the The Project Proponent shall keep the plinth level of the building blocks sufficiently
- VXV The project proponent shall construct a sedimentation basin in the lower level of the project site to trap pollutant and other wastes during rains.

 The project proponent shall provide proper rasta of proper width and proper strength
- Water recharge arrangements, Storm water drainage system, Solid waste management site and provision for treatment of bio-degradable waste, STP, water supply line, dual plumbing line, electric supply lines etc. and shall offer possession of the units/flats for the project before the start of construction.

 The project proponent shall develop complete civic infrastructure Plotted colony including internal roads, green belt development, sewerage line, Rain of the Residential
- xxviii. The project proponent shall provide fire control room and fire officer for building
- above 30 meter as per National Building Code.

 The site for solid waste management plant be earmarked on the layout plan and the the Authority within one month detailed project for setting up the solid waste management plant shall be submitted to
- XXX The project proponent shall discharge excess of treated waste water/storm water in the public drainage system and shall seek permission of HUDA before the start of
- XXXI. The project proponent shall maintain the distance between STP and water supply line.
- XXXII The project proponent shall ensure that the stack height is 6 meter more than the
- XXXIII should be used. For disinfection of the treated wastewater ultra-violet radiation or ozonization process
- xxxiv The project proponent shall strive to minimize water in irrigation of landscape by minimizing grass area, using native variety, xeriscaping and mulching, utilizing efficient irrigation system, scheduling irrigation only after checking evapotranspiration data.
- VXXV Halon free fire suppression system. The Project Proponent shall use zero ozone depleting potential material in insulation, refrigeration, air-conditioning and adhesive. Project Proponent shall also provide
- Standards for discharge of environmental pollutants as enshrined in various schedules of rule 3 of Environment Protection Rule 1986 shall be strictly complied with.
- xxxvii. The project proponent shall ensure that the of DG sets is more than the highest tower and also ensure that the emission standards of noise and air are within the CPCB latest as per CPCB latest standards for high capacity DG sets. prescribed limits. Noise and Emission level of DG sets greater than 800 KVA shall be
- XXXVIII. between 0.98 lag to 1 at the point of connection. All electric supply exceeding 100 amp, 3 phase shall maintain the power factor
- xxxix. reduce water consumption. Further temperature, relative humidity during summer and winter seasons should be kept at optimal level. Variable speed drive, best Co-efficient HVAC system should be adopted and only treated water shall be used by project proponent for cooling, if it is at all needed. The Project Proponent shall also use evaporative cooling technology and double stage cooling system for HVAC in order to of Performance (Cop), as well as optimal Integrated Point Load Value and minimum outside fresh air supply may be resorted for conservation of power and water. Coil type cooling DG Sets shall be used for saving cooling water consumption for water cooled The project proponent shall not use fresh water for HVAC and DG cooling. Air based relative humidity during summer and
- × proponent shall obtain manufacturer's certificate also for that. The project proponent shall ensure that the transformer is constructed with high quality grain oriented, low loss silicon steel and virgin electrolyte grade copper. The project
- xli. wash under any meteorological conditions sufficiently high. Stack shall be designed in such a way that there is no stack downproject proponent shall ensure that exit velocity from the stack should be
- xlii. issuance of EC letter. The environment clearance conditions applicable till life space project in case of Residential project will continue to apply. The resident welfare association/Housing co-operative societies shall responsible to comply conditions laid The validity of this environment clearance letter is valid up to 7 years from the date of

xliii. down in EC. In case of violation the action would be taken as per the laid down law of land. Compliance report should be sent to this office till life of the project. If project is not completed within the validity period then the project proponent shall submit the application for extension of validity within one month before the lapse of validity period of Environment Clearance i.e. 7 years. The project proponent should intimate to the Authority well before shifting their address of communication.

xliv.

Chairman,

Assessment Authority, Haryana, Panchkula State Level Environment Impact

Endst. No. SEIAA/HR/2019/

Dated:....

- - A copy of the above is forwarded to the following:
 The Additional Director (IA Division), MoEF&CC, Gol, Indra Paryavaran Bhavan, Zor bagh Road-New Delhi.
 The Regional office, Ministry of Environment, Forests & Climate Change, Govt. of India, Bay's no. 24-25, Sector 31-A, Dakshin Marg, Chandigarh.
 The Chairman, Haryana State Pollution Control Board, C-11, Sector-6, Pkl.
- 2.
- ω

Chairman,

State Level Environment Impact Assessment Authority, Haryana, Panchkula.